

Sikagard® High Gloss Sealer Acrylic surface sealer



An acrylic sealer for concrete and masonry that dries to a clear, glossy finish and provides protection against moisture and mild corrosives. Ideal for retaining walls.



Advantages

- Roll, brush or spray applied
- Improves dirt resistance
- **Protects from mild corrosives**
- Protects from de-icing salts
- Adds sheen to surface appearance
- Keeps substrates looking new longer

Typical Data

Shelf Life: 1 year in original unopened packaging

Storage Conditions: Store dry at 45°-90°F (7°-32°C). Keep from freezing.

Condition material to 65-75F (18-24C) before using.

Color: White (dries clear)

VOC: 41 g/l

Dry Time: Approximately 4-8 hrs. Wait 24 hrs. before exposing to foot/car traffic. Approximately 72 hrs. for maximum water repellency, depending on surface







SIKA CORPORATION

201 Polito Avenue Lyndhurst, NJ 07071 Phone: 800-933-7452 Fax: 201-933-6225 Toll Free: 800.933.SIKA Fax: 514-694-2792

usa.sika.com

SIKA CANADA INC.

601 Delmar Avenue Pointe Claire Quebec H9R 4A9 Phone: 514-697-2610

SIKA MEXICANA S.A. DE C.V.

Carretera Libre Celaya Km. 8.5 Fracc. Industrial Balvanera Corregidora, Queretaro C.P. 76920

Phone: 52 442 2385800 Fax: 52 442 2250537

