



# REFURBISHMENT COMMERCIAL

## Professional Coatings



# PROFESSIONAL COATINGS THAT BEAU

## Sikagard® 670W

High Performance Water-based, 100% acrylic protective anti-carbonation coating.

A high- quality, professional grade coating that enhances the appearance of almost any structure. Waterproofs and protects from environmental elements and natural weathering. Its ease of application and excellent coverage make Sikagard 670W extremely user-friendly for professional contractors.

Use Sikagard 670W to “weatherproof” and protect - as well as enhance the look - of exposed structures where cracks and movement are typically not a concern.

### ADVANTAGES

- ▲ Easy to apply, contractor-friendly
- ▲ Extremely resistant to dirt pick up
- ▲ Ideal for most structures
- ▲ Excellent weathering resistance
- ▲ Excellent UV Resistance
- ▲ Excellent adhesion
- ▲ Great Color Retention
- ▲ Breathable - resists peeling and blistering

### APPLICATIONS

- ▲ Building facades and balconies
- ▲ Precast concrete elements
- ▲ Bridge abutments/parapets
- ▲ Parking structures
- ▲ Civil Engineering structures

### KEY DATA

- ▲ Number of coats: 2
- ▲ Dry film thickness per coat: 2.5 mils
- ▲ Coverage rate per coat: 300 sq. ft/gal
- ▲ Dry time 60°F (20°C) and 50% RH  
Between Coats: 30 in  
Rain Resistant: 1 hour  
Finally Drying: 4 hours



**1-2** Sikagard 670W enhances the appearance of architectural concrete designs

**3** Sikagard 670w protects concrete structures from the elements... for years to come

## Sikagard® 550W

High Performance Elastomeric, anti-carbonation, crack-bridging, water-based acrylic protective coating

When cracks are a concern, Sikagard 550W Elastocolor is the contractor's choice. This top-quality, professional grade elastomeric coating is able to bridge fine cracks and enhance the appearance of almost any structure. Sikagard 550W Elastocolor is completely waterproof and protects the structure even in harsh environments

### ADVANTAGES

- ▲ Bridges hairline cracks-even at low temps
- ▲ Easy to apply, sprayable
- ▲ Ideal for most structures
- ▲ Excellent adhesion
- ▲ Breathable - resists peeling and blistering
- ▲ Extremely resistant to dirt pick-up
- ▲ Blocks carbonation in concrete
- ▲ Excellent UV Resistance

### APPLICATIONS

- ▲ Building facades and balconies
- ▲ Cast-in-place concrete (subject to shrinkage cracking)
- ▲ Parking structures
- ▲ Civil Engineering structures

### KEY DATA

- ▲ Number of coats: 2
- ▲ Dry film thickness per coat: 8 mils
- ▲ Coverage rate per coat: 100 sq. ft/gal
- ▲ Dry time 68°F (20°C) and 50% RH
  - To touch: (recoat time) 8 hours
  - Rain Resistant: 4 hour
  - Final cure: less than 24 hours
- ▲ Max. crack width: 1/16 inch



**1** Sikagard 550W Elastocolor providing crack-bridging protection and color enhancement for over ten years and counting...

**3** Sikagard 550W Elastocolor beautifies this structure, while providing a carbon dioxide barrier to protect against steel corrosion



## Both Sikagard 550W Elastocolor and Sikagard 670W are part of the Sika ColorWorks Program.

The most professional color-matching program in the industry - ColorWorks provides a choice of over 400 colors, produced in the factory or tinted locally by a Sika authorized distributor. ColorWorks can also match any custom color requirement, providing quick-turn-around of wet samples to ensure an acceptable match. When it comes to color, don't settle. Get the color you want, when you need it, with Sika's ColorWorks program.



All sales of Sika products are subject to Sika's current Terms and Conditions of Sale available at [www.sikausa.com](http://www.sikausa.com) or by calling 201-933-8800. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Product Data Sheet, product label and Material Safety Data Sheet, which are available at [www.sikausa.com](http://www.sikausa.com) or by calling Technical Services at 1-800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instructions for each Sika product as set forth in the current Product Data Sheet, product label and Material Safety Data Sheet prior to product use.

The sale of all Sika products are subject to the following Limited Warranty:

### LIMITED MATERIAL WARRANTY

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Our most current General Sales Conditions shall apply. Please consult the Product Data Sheets prior to any use and processing.



**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 201-933-8800  
Toll Free: 800.933.SIKA  
Fax: 201-933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Canada Inc.**  
601 Delmar Avenue  
Pointe Claire  
Quebec H9R 4A9  
Phone: 514-697-2610  
Fax: 514-694-2792

**Sika Mexicana S.A. de C.V.**  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537

