



# SikaLevel® Primer

**CONCRETE PRIMER AND SEALER FOR USE WITH  
SIKALEVEL SELF LEVELING UNDERLAYMENT**



## WHERE TO USE:

- Use as a primer/sealer for absorbent substrates including concrete and cement screeds. Particularly suitable as an adhesion promoter and surface sealer beneath SikaLevel Underlayment enhancing the bond and integrity of the underlayment when applied onto porous substrates.



**PRO  
SELECT**

### ADVANTAGES

- Ready to use, no dilution required
- Water-based and solvent-free
- Penetrates substrate to reduce outgassing and formation of bubbles in the underlayment
- Prevents water loss from the underlayment into the substrate
- Quick-drying and fast film formation to increase productivity
- Achieves excellent bond values throughout the recommended range of application temperatures

### TECHNICAL DATA

- Shelf Life: 2 years in original, unopened container. Protect from high heat and freezing.
- Storage Conditions: Store dry at 40°-77°F (5°-25°C).
- Condition material to 65°-75°F (18°-24°C) before using
- Drying Time: 2 hours or less
- Recoat Time: Allow previous coats to become tack-free before applying additional coats
- Bond Strength: 217 psi (1.5 MPa)(substrate failure)
- VOC (EPA method 24): 10 g/L
- Specific Gravity: approx. 1.02 kg/ltr.



### FOR MORE INFORMATION:

Contact Sika: Phone 800.933.7452 Website: [www.usa.sika.com/retail](http://www.usa.sika.com/retail)

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 201-933-8800  
Fax: 201-933-6225

