



SikaBond® Construction Adhesive
 One part advanced polyurethane,
 elastomeric sealant/adhesive



A one-component, gun-grade, adhesive and sealing compound of permanent elasticity. This dual-purpose material is based on a special moisture-cured polyurethane with an accelerated curing time.



Advantages

- Permanently elastic
- Water immersible after cure
- Bonds pavers, caps, roofing, concrete, wood, tile, aluminum, foam, mirrors and more
- Paintable, stainable and sandable
- Waterproof after cure
- USDA approved

Typical Data

Shelf Life : 1 year (10.1 oz.) / 9 moths (29 oz.) in original unopened packaging

Storage Conditions : Store at 40°F-95°F (4°-35°C).

Condition material to 65°F-75°F (18°-24°C) before using.

Color : Gray

Application Temperature : -40°F -100°F .

Service Range : -40°F to 170°F.

VOC : 28.5 g/l

Curing Rate : Tack-free time (TT-S_00230C) 1 to 2 hours depending on climate.

Final cure : 3 to 5 days

Tensile Properties (ASTM D-412)

Tensile Stress	225 psi
Elongation at Break	600%

Weathering Resistance : Excellent

Chemical Resistance : Good resistance to water, weak acids, weak alkalis, sewerage, mineral oils, vegetable oils, fats, fuels.(Not resistant to organic solvents, paint thinner, strong acids, strong alkalis). Consult Technical Service for specific data.



SIKA CORPORATION
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225
Toll Free : 800.933.SIKA
usa.sika.com

SIKA CANADA INC.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

SIKA MEXICANA S.A. DE C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537

BUILDING TRUST

