



**Sikasil® Builders' Silicone**  
Neutral cure, one-component, building  
silicone



Neutral cure silicone for sealing expansion and control joints. Ideal for window and door perimeters, skylights, conventional glazing, and other building components.



## Advantages

- High heat and UV resistance
- Bonds to glass, concrete, masonry, tile and more
- Vertical and horizontal applications possible
- Low odor
- Water and weather resistant
- Clear to easily blend with any substrate

## Typical Data

**Shelf Life :** 1 year in original unopened packaging

**Storage Conditions :** Store in unopened containers at temperatures lower than 80°F (27°C).

**Color :** Clear

**VOC Content :** 36 g/L

**Skin Time (MNA method) :** 20 minutes

**Cure Time (ASTM C-679) :** 24 hours (depending on temperature and humidity will slow the cure of the sealant)

**Non-sag Properties (ASTM C-639) :** non-sag

**Tack Free Time (ASTM C-639) :** 30 min

**Movement Capability (ASTM C-719)** ± 25%

**Weathering Resistance :** Excellent

**Application Temperature :** -35°F -140°F.

**Service Temperature Range :** -80° to 350°F.



**SIKA CORPORATION**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 800-933-7452  
Fax: 201-933-6225  
Toll Free : 800.933.SIKA  
usa.sika.com

**SIKA CANADA INC.**  
601 Delmar Avenue  
Pointe Claire  
Quebec H9R 4A9  
Phone: 514-697-2610  
Fax: 514-694-2792

**SIKA MEXICANA S.A. DE C.V.**  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537

**BUILDING TRUST**

