



# Sika® MaxTack

Interior, water-based, fast grab adhesive



A one-component, fast grab, high strength, water-based adhesive used for interior building applications.



## Advantages

- High strength
- Durable
- Bonds to most substrates, including concrete, mortar, wood, etc.
- Eliminates the need for nails and screws
- Low odor
- Easy clean up

## Typical Data

**Shelf Life :** 18 months in original unopened packaging

**Storage Conditions :** Store at in dry conditions and protected from direct sunlight at temperatures between +50°F(+10°C) and +77°F (+25°C)

**Color :** Cream

**Substrate Temperature :** 41°F -86°F

**Ambient Temperature :** 41°F -95°F

**VOC :** <40 g/l

**Skin Time :** ~ 30 minutes

**Curing Rate :** 0.25 in/ 24 hrs

**Final Cure :** 48 hrs



**SIKA CORPORATION**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: 800-933-7452  
Fax: 201-933-6225  
Toll Free : 800.933.SIKA  
usa.sika.com

**SIKA CANADA INC.**  
601 Delmar Avenue  
Pointe Claire  
Quebec H9R 4A9  
Phone: 514-697-2610  
Fax: 514-694-2792

**SIKA MEXICANA S.A. DE C.V.**  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537

**BUILDING TRUST**

