




SikaBond®-150 Premium Floor

UNIVERSAL PRESSURE SENSITIVE ACRYLIC ADHESIVES FOR ALL FLEXIBLE COVERINGS

- Extraordinary strength for both wet tack and pressure sensitive applications
- Up to a 8 hour working time
- Easy to apply with a quick flash-off time
- High coverage with excellent trowelability
- Solvent-free low odor formula

Packaging available

4 gal. Plastic Pail (15.14L)



BUILDING TRUST



SikaBond®-150 Premium Floor

UNIVERSAL PRESSURE SENSITIVE ACRYLIC ADHESIVES FOR ALL FLEXIBLE COVERINGS

WHERE TO USE

SikaBond®-150 Premium Floor is a 1-component, solvent-free, universal pressure-sensitive dispersion adhesive. SikaBond®-150 Premium Floor is designed for full surface bonding of mentioned below floor coverings on absorbent and non-absorbent substrates in interior areas: luxury vinyl tiles (LVT), woven fabrics, linoleum coverings, single or multilayer needle felting, natural fibre coverings with backing, impact sound insulation underlays, carpets with PVC/PU/filler-free backing, corkment and cork linoleum, PVC and cushioned vinyl (CV) floor coverings, rubber floor coverings in sheets, and rubber floor coverings as tiles.



TYPICAL DATA (Material and curing conditions @ 73°F (23°C) and 50% R.H.)	
Shelf Life	12 months from date of production if stored in undamaged original sealed containers
Chemistry	1-Component dispersion
Coverage	See trowel guide
Flash-off Time	0-120 minutes (depending on laying method and porosity)
Working Time	20 min-8 hrs (depending on laying method and porosity)
Cure Time	24 hrs (final strength after 72 hrs)
Substrate Moisture Content	9 lbs. / 1000 sq.ft. / 24 hrs or 90% RH or 6 lbs. / 85% RH prior to install linoleum or rubber)
VOC	0 g/L (measured per SCAQMD rule 1168)
Density	75 lbs./ft ³ (1.20 kg/l)

FEATURES AND BENEFITS

- Very easily spread
- Up to a 8 hour working time
- Low consumption / high coverage
- High initial adhesion power
- Suitable for wet and semi-wet bonding
- Suitable for use with underfloor heating
- Suitable for use with castor-chairs
- Suitable for shampooing
- Suitable for difficult coverings

NOTE: Always refer to Current Product data Sheet and SDS for detailed performance specifications prior to use.

TROWEL GUIDE

Flooring Type	Trowel	Coverage
Luxury vinyl tiles (LVT), woven fabrics, natural fiber coverings with backing, impact sound insulation underlayments, carpets with PVC/PU/filler-free backing, corkment, cork linoleum, PVC and cushioned vinyl (CV) floor coverings, rubber floor coverings in sheets, and rubber floor coverings as tiles.	1/16" x 1/32" x 1/32" U-Notch 	220-260 sq.ft. per gal.
Linoleum coverings, sheet goods	1/16" x 1/16" x 1/16" Square Notch 	150-180 sq.ft. per gal.
Textile floor coverings, needle felting		



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.usa.sika.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225



BUILDING TRUST

