



FOR NON-POROUS
SUBSTRATES

Sika® Level-02 EZ Primer

ACRYLIC PRIMER FOR NON ABSORBENT SUBSTRATES

- One component
- Excellent primer for difficult substrates
- Ideal on epoxy, ceramic tiles, old vinyl, linoleum, rubber and other coverings
- Compatible with Sika® Level products

Available in
1 gal.pail



BUILDING TRUST



Sika® Level-02 EZ Primer

ACRYLIC PRIMER FOR NON ABSORBENT SUBSTRATES

WHERE TO USE

- Interior only
- Terrazzo, ceramic tiles, natural stone
- Old substrates with water-resistant adhesive residues
- Fully-bonded old elastic coverings
- Old sealed / coated substrates

NOTE: Always refer to current PDS and SDS for detailed performance specifications prior to use.





















TYPICAL DATA (Material and curing conditions @ 73°F (23°C) and 50% R.H.)

Color	Mint
Chemistry	Acrylic
Density (ASTM C185)	81 lbs/cu.ft.
Drying Time	1 - 2 hours
Coverage	350 - 500 sq.ft. per 1 gallon

FEATURES AND BENEFITS

- Provides optimum adhesion
- Ready-to-use, no dilution required
- Quick dry time
- Solvent free
- Suitable for application on subfloor radiant system
- Low consumption of material
- Low VOC

Sika® Classification Chart

Flow					
Speed					
For Porous					
For Non-Porous					



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.sikasecure.com

Sika Corporation
 201 Polito Avenue
 Lyndhurst, NJ 07071
 Phone: 201-933-8800
 Fax: 201-933-6225



BUILDING TRUST

