

# PRODUCT DATA SHEET

## RhinoBond PS

---

RHINOBOND PS CARDBOARD DISC IS A ROUND COATED CARDBOARD DISC

---

### PRODUCT DESCRIPTION

RhinoBond PS Cardboard Disc is a round coated cardboard disc used in the installation of Sarnafil® S 327 or Sikaplan® RhinoBond roofing systems. It is intended to protect Sika approved polystyrene fanfold roofing underlayments from heat during the induction welding process.

### USES

Used between the Sarnadisc RhinoBond plate and the Sika approved polystyrene fanfold roofing underlayment with polymeric film facer.

#### Areas of Application

- Recover Roofs
- New Roofs
- Recover Applications

### CHARACTERISTICS / ADVANTAGES

- Protects the Sika approved polystyrene fanfold roofing underlayment from heat during the induction welding process
- Specially designed for use with Sarnadisc RhinoBond plates
- Pre-punched center hole for easy application
- Fast and easy to install

## PRODUCT INFORMATION

<b>Chemical Base</b>	50 pt coated cardboard
<b>Packaging</b>	250 per box, 4 lb (1.8 kg) per box
<b>Appearance / Color</b>	White
<b>Shelf Life</b>	N/A
<b>Storage Conditions</b>	N/A
<b>Dimensions</b>	Diameter: 4" (102 mm) round disc Thickness: 0.050" (1.2 mm)

## APPLICATION INSTRUCTIONS

### APPLICATION

Position the RhinoBond® PS Cardboard Disc on the surface of the Sika approved fanfold roofing underlayment at the designated spacing. Center the Sarnadisc® RhinoBond plate over the RhinoBond® PS Cardboard Disc so the center holes are aligned. Insert the Sikaplan® fastener through the center holes and fastened to the approved roof deck, clamping the fanfold roofing underlayment in place.

## AVAILABILITY/WARRANTY

### Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

### Warranty

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Sarnafil**  
100 Dan Road  
Canton, MA 02021  
Phone: +1 800-451-2504  
Fax: +1 781-828-5365  
[usa.sarnafil.sika.com](http://usa.sarnafil.sika.com)  
[webmaster.sarnafil@us.sika.com](mailto:webmaster.sarnafil@us.sika.com)

**Sika Mexicana S.A. de C.V.**  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



Product Data Sheet  
RhinoBond PS  
September 2019, Version 03.01  
020945051100002033

RhinoBondPS-en-US-(09-2019)-3-1.pdf

