

## PRODUCT DATA SHEET

# Sika® MultiSeal-505

Sika® MultiSeal-505 is a prefabricated self-adhering sheet-type waterproofing membrane

### PRODUCT DESCRIPTION

Sika® MultiSeal-505 is a prefabricated self-adhering sheet-type waterproofing membrane. It is composed of a high-tensile polyester film that is coated with a layer of specially formulated rubberized asphalt adhesive. A release sheet protects the asphalt and is removed as the membrane is installed. Sika® MultiSeal-505 is engineered to be a multi-purpose waterproofing sheet suitable for use under siding and exterior plaster. Sika® MultiSeal-505 adheres aggressively to most clean, dry substrates including metal, wood vinyl and masonry. The special Sika® MultiSeal-505 polymer modified waterproofing compound self-seals around punctures such as nails, screws and staples. This advanced system bonds to the substrate and seals around fasteners to help prevent damage caused by water penetration.

### USES

- Underlayment for stucco at head, sill, chimney shoulder, pot shelves, parapets, pony walls and other general waterproofing applications
- Thru-wall flashing in cavity wall construction

### PRODUCT INFORMATION

<b>Packaging</b>	Carton contains 3 x 12", 2 x 18" wide rolls. (225 sf/ carton)
<b>Appearance / Color</b>	Black
<b>Shelf Life</b>	1 Year
<b>Storage Conditions</b>	Store upright in original, unopened and undamaged sealed packing in dry conditions. Do not expose to direct sunlight or other heat sources.
<b>Dimensions</b>	12", 18" wide x 75' long rolls.

<b>Thickness</b>	40 Mils Nom.	(MFM-THK-01)
<b>Tensile Strength</b>	Machine Direction	34.5 lbf/in
	Cross Machine Direction	43.5 lbf/in
<b>Elongation at Break</b>	Machine Direction	160%
	Cross Machine Direction	109%
<b>Adhesion in Peel</b>	18.5 lbf/in [@73°F]	(MFM-PA180-05)
<b>Low Temperature Bend</b>	Pass [@-20°F]	(MFM-BD-13)
<b>Ambient Air Temperature</b>	>50°F	
<b>Substrate Temperature</b>	>50°F	

#### SUBSTRATE PREPARATION

- Apply in clear, dry weather
- Surface must be clean, dry and free from oil
- Masonry must be clean, fully cured and primed with an asphalt primer
- Prime weathered surfaces as necessary – clean, dry, wood and metal surfaces do not require priming

#### APPLICATION METHOD / TOOLS

- Use 3" side laps and 6" head laps
- Apply uniform pressure with a 2-3" hand roller to entire surface

#### LIMITATIONS

- Do not install over solvent-based sealants unless fully cured – active solvents may liquefy bottom adhesive surface
- Installer is responsible for compatibility with caulks and sealants
- Do not install over flexible vinyl gaskets
- Do not expose installed product to direct sunlight for more than 90 days

#### BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

#### OTHER RESTRICTIONS

See Legal Disclaimer.

# ENVIRONMENTAL, HEALTH AND SAFETY

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Mexicana S.A. de C.V.**  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



**Product Data Sheet**  
Sika® MultiSeal-505  
August 2018, Version 01.02  
020511090000000033

SikaMultiSeal-505-en-US-(08-2018)-1-2.pdf

