

**SECTION 1. IDENTIFICATION**

Product name : Sikalastic®-710 Base Lo-VOC

Company name : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Flammable liquids : Category 3


Respiratory sensitization : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.  
H317 May cause an allergic skin reaction.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



H350 May cause cancer by inhalation.  
H372 Causes damage to organs through prolonged or repeated exposure if inhaled.

Precautionary Statements :

**Prevention:**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P284 Wear respiratory protection.

**Response:**

- P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P308 + P313 IF exposed or concerned: Get medical advice/ attention.
- P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
- P362 + P364 Take off contaminated clothing and wash it before reuse.
- P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage:**

- P403 + P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.

**Disposal:**

- P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labeling**

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

**Other hazards**

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.




---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**
**Mixtures****Components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Solvent naphtha (petroleum), medium aliph.	64742-88-7	Flam. Liq. 3; H226 STOT RE 1; H372 Asp. Tox. 1; H304	>= 5 - < 10
Quartz (SiO <sub>2</sub> )	14808-60-7	Carc. 1A; H350i STOT RE 1; H372 STOT SE 3; H335	>= 1 - < 5
4-methyl-m-phenylene diisocyanate	584-84-9	Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

---

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : sensitizing effects  
Asthmatic appearance  
Allergic reactions  
May cause an allergic skin reaction.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.



May cause cancer by inhalation.  
 Causes damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
 Carbon dioxide (CO2)  
 Dry chemical
- Unsuitable extinguishing media : Water
- Further information : Use water spray to cool unopened containers.  
 Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
 Remove all sources of ignition.  
 Deny access to unprotected persons.  
 Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
 If the product contaminates rivers and lakes or drains inform respective authorities.  
 Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
 Take precautionary measures against electrostatic discharges.
- Advice on safe handling : Avoid formation of aerosol.



Do not breathe vapors or spray mist.  
 Avoid exceeding the given occupational exposure limits (see section 8).  
 Do not get in eyes, on skin, or on clothing.  
 For personal protection see section 8.  
 Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharge.  
 Open drum carefully as content may be under pressure.  
 Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
 Follow standard hygiene measures when handling chemical products.

- Conditions for safe storage : Store in original container.  
 Keep in a well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Store in accordance with local regulations.
- Materials to avoid : Explosives  
 Oxidizing agents  
 Poisonous gases  
 Poisonous liquids
- Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Respirable fraction)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Res-	0.025 mg/m <sup>3</sup>	ACGIH



		pirable fraction)	(Silica)	
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable fraction)	0.025 mg/m3	ACGIH
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
4-methyl-m-phenylene diisocyanate	584-84-9	C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.  
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.  
  
The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection  
Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-



essary.

- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

---

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : viscous liquid
- Color : gray
- Odor : mild, aromatic
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : 135 °F / 57 °C  
(Method: Tag closed cup)
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapor pressure : 0.01 hpa
- Relative vapor density : No data available



Density	:	1.29 g/cm <sup>3</sup> (73 °F / 23 °C)
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	97.5 g/l

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	No data available

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Components:****4-methyl-m-phenylene diisocyanate:**

Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0.107 mg/l Exposure time: 4 h Test atmosphere: vapor





Acute dermal toxicity : LD50 Dermal (Rat): > 9,400 mg/kg

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization**

**Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer by inhalation.

**Product:**

Carcinogenicity - Assessment : Positive evidence from human epidemiological studies (inhalation)

<b>IARC</b>	Group 1: Carcinogenic to humans Quartz (SiO <sub>2</sub> ) (Silica dust, crystalline)	14808-60-7
	Group 2B: Possibly carcinogenic to humans titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans 4-methyl-m-phenylene diisocyanate (toluene diisocyanates)	584-84-9
	Group 2B: Possibly carcinogenic to humans carbon black	1333-86-4
<b>OSHA</b>	Not applicable	
<b>NTP</b>	Reasonably anticipated to be a human carcinogen 4-methyl-m-phenylene diisocyanate	584-84-9
	Known to be human carcinogen Quartz (SiO <sub>2</sub> ) (Silica, Crystalline (Respirable Size))	14808-60-7

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs through prolonged or repeated exposure if inhaled.



Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Product:**

Routes of exposure : Inhalation  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

**Aspiration toxicity**

Not classified based on available information.

**Further information**

**Product:**

Remarks : Titanium dioxide (13463-67-7)  
In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

**Product:**



Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

**SECTION 14. TRANSPORT INFORMATION**

**International Regulations**

**IATA-DGR**

UN/ID No. : UN 1263  
 Proper shipping name : Paint  
 Class : 3  
 Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

**Domestic regulation**

**49 CFR**

UN/ID/NA number : UN 1263  
 Proper shipping name : Paint  
 Class : 3  
 Packing group : III  
 Labels : FLAMMABLE LIQUID  
 ERG Code : 128  
 Marine pollutant : no



DOT: As per 49CFR 173.150 (f) Combustible Liquid Exception, Material is Not Regulated.  
 IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

#### EPCRA - Emergency Planning and Community Right-to-Know

##### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

##### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
 Respiratory or skin sensitization  
 Carcinogenicity  
 Specific target organ toxicity (single or repeated exposure)

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

4-methyl-m-phenylene diisocyanate	584-84-9	>= 0.1 - < 1 %
-----------------------------------	----------	----------------

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**California Prop 65**  WARNING: Cancer – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

**Sikalastic®-710 Base Lo-VOC**



Revision Date 07/10/2019

Print Date 07/10/2019

	its for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / STEL	: Short-term exposure limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-1 / C	: Ceiling
OSHA Z-3 / TWA	: 8-hour time weighted average

**Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 07/10/2019

10000008088

US / Z8