



SikaQuick® EZ PATCH

FAST-SETTING MATERIAL USED FOR PATCHING OF CONCRETE SURFACES AND SLOPES

- Easy to use, one-component
- Variable water ratios for different use: resurfacing/sloping
- Interior and exterior use
- Feather edge application

Available in
Bag
30 lbs.



BUILDING TRUST



SikaQuick® EZ PATCH

HIGH PERFORMANCE, FAST SETTING, CEMENT BASED PATCH

APPLICATIONS

- Used to reprofile substrates or subfloor surfaces from feather edge to 1-1/2" (38 mm).
- Repair minor defects, holes, cracks and pre-fill nonmoving joints and seams in concrete, balconies, terrace, etc.
- On grade, above and below grade on concrete and mortar.
- On horizontal surfaces.
- As an overlay system for topping/resurfacing concrete.

TYPICAL DATA

- Shelf Life: One year in original, unopened bags
 - Storage Conditions: Store dry at 45°-95°F (7°-35°C)
 - Color: Gray powder
 - Yield: 12-15 ft² at 1/4" (1.1-1.4 m² at 6 mm) per bag
 - Waiting Time / Overcoating: 16 - 24 hours
 - 28 days compressive strength (ASTM C-109) - 4,000 psi (27.6 MPa)
 - Layer Thickness
- | | Min. | Max. |
|----------|------------------|------------------|
| Neat | FE | 1-1/2" (38.1 mm) |
| Extended | 1-1/2" (38.1 mm) | 3" (76.2 mm) |

BENEFITS

- Easy to use, one-component.
- Variable water ratios for different use: resurfacing/sloping.
- Interior and exterior use.
- Feather edge application.
- High compressive and flexural strengths.
- High abrasion resistance.
- Increased freeze/thaw durability.

LITERATURE

- Product Data Sheet
 - Safety Data Sheet
 - CSI Specification
- *Always refer to Current Product Data Sheet and SDS for detailed performance specifications prior to use.



Note: Advice on specific applications is available from the Technical Service Department of Sika Construction Products Division.

FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.usa.sika.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225

BUILDING TRUST

