



## PRODUCT DATA SHEET

# Sarnafastener #14

---

Sarnafastener #14 is a threaded drill point fastener

---

### PRODUCT DESCRIPTION

Sarnafastener #14 is a threaded drill point fastener used within Sarnafil® roof systems to attach Sarnafil S 327 Membrane or Sarnatherm® insulation, Sarnatherm roof boards, gypsum roof boards, or other Sika approved boards into structural concrete (140 - 150 lb/ft), wood plank (min. 1-1/2"), or wood sheathing (> 15/32").

### USES

Used in conjunction with Sarnadiscs, Sarnarail, Sarnabars, or Sarnaplates for attachment direct to the roof deck.

#### Areas of Application

- New Roof Applications
- Reroof Applications
- Recover Applications

### CHARACTERISTICS / ADVANTAGES

- Deep threads for high pullout resistance.
- Extra sharp spade point for quick installation in new or reroof applications.
- In concrete applications, fastener may be reversed out of predrilled hole without damaging the deck.

### APPROVALS / STANDARDS

- Factory Mutual 4470
- Miami-Dade County

## PRODUCT INFORMATION

**Chemical Base** Made from carbon steel, treated with a corrosion-resistant coating to meet the criteria for corrosion resistance.

Packaging	Length	Thread	Packaging	Weight
	1-1/4" (32 mm)	Full	1000 / Pail	12 lb (5.4 kg)
	1-3/4" (44 mm)	Full	1000 / Pail	16 lb (7.3 kg)
	2" (51 mm)	Full	1000 / Pail	18 lb (8.2 kg)
	3" (76 mm)	Full	1000 / Pail	26 lb (11.8 kg)
	4" (102 mm)	3" (76 mm)	1000 / Pail	34 lb (15.4 kg)
	5" (127 mm)	4" (102 mm)	500 / Pail	22 lb (10.0 kg)
	6" (152 mm)	4" (102 mm)	500 / Pail	26 lb (11.8 kg)
	7" (178 mm)	4" (102 mm)	500 / Pail	30 lb (13.6 kg)
	8" (203 mm)	4" (102 mm)	500 / Pail	34 lb (15.4 kg)
	9" (228 mm)	4" (102 mm)	500 / Pail	37 lb (16.8 kg)
	10" (254 mm)	4" (102 mm)	500 / Pail	40 lb (18.1 kg)
	11" (279 mm)	4" (102 mm)	500 / Pail	44 lb (20.0 kg)
	12" (305 mm)	4" (102 mm)	250 / Pail	25 lb (11.3 kg)
	14" (356 mm)	4" (102 mm)	250 / Box	29 lb (13.2 kg)

\* One #3 Phillips drive bit is included in each box.

**Appearance / Color** Gray

**Shelf Life** N/A

**Storage Conditions** N/A

**Dimensions**

- Thread Diameter: 0.245" (6.2 mm)
- Shank Diameter: 0.190" (4.8 mm)
- Head Diameter: 0.435" (11 mm)
- Head Style: #3 Phillips

## APPLICATION INSTRUCTIONS

### APPLICATION

The Sarnafastener #14 is fastened straight into the roof deck with a heavy-duty (4 amp minimum), variable speed (0 - 2500 rpm), reversible screwgun with a clutch release and a #3 Phillips drive bit. Sikaplan Fastener #14 must penetrate concrete\* and wood plank roof decks by 1" (25 mm) and the underside of wood sheathing roof decks by a 1/2" (13 mm). Care must be taken not to damage the roof deck. Choose the correct fastener length and do not overdrive or underdrive the fastener. Pullout tests are required prior to job start when used with existing wood sheathing roof decks or structural concrete roof decks for technical evaluation.

\*Pre-drill a 3/16" (4.8 mm) pilot hole at least 1/2" (13 mm) deeper than fastener embedment.

### MAINTENANCE

Standard maintenance of Sarnafil® or Sikaplan® systems should include inspections of flashings, drains, and

termination sealants at least twice a year and after each storm.

### AVAILABILITY/WARRANTY

#### Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

#### Warranty

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator

### BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

### OTHER RESTRICTIONS

See Legal Disclaimer.

Product Data Sheet  
Sarnafastener #14  
September 2019, Version 03.01  
020945051100001013

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

### Sika Sarnafil

100 Dan Road  
Canton, MA 02021  
Phone: +1 800-451-2504  
Fax: +1 781-828-5365  
[usa.sika.com/sarnafil](http://usa.sika.com/sarnafil)  
[webmaster.sarnafil@us.sika.com](mailto:webmaster.sarnafil@us.sika.com)

### Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



### Product Data Sheet

Sarnafastener #14  
September 2019, Version 03.01  
020945051100001013

Sarnafastener14-en-US-(09-2019)-3-1.pdf

