



SikaLevel®-025 Patch

RAPID SETTING, POLYMER MODIFIED, CEMENT-BASED FLOWABLE PATCHING COMPOUND

- For use on concrete and plywood substrates
- Levels and smooths substrates prior to the installation of floor covering
- Ideal for patching and leveling from 1/16" to 1/2"
- Apply over properly prepared cutback, embossed resilient vinyl floors and existing ceramic tile
- Fast drying, foot traffic in 30 to 60 minutes
- **Color:** Gray
- **Packaging:** 25 lb. bags

Attributes Include:



BUILDING TRUST



SikaLevel[®]-025 Patch

RAPID SETTING, POLYMER MODIFIED, CEMENT-BASED FLOWABLE PATCHING COMPOUND

WHERE TO USE

WHEN MIXED WITH WATER:

- Properly prepared cutback and carpet adhesive residue
- Fully bonded, properly prepared ceramic and porcelain tile
- A single layer of properly prepared, fully bonded VCT and felt-backed sheet vinyl
- Can be installed over a substrate measuring less than 98% RH and allowed to dry 18 hours prior to encapsulation

WHEN MIXED WITH SIKA[®] LATEX R:

- Mix SikaLevel[®]-025 Patch with Sika[®] Latex R and use as an embossing leveler or as a patch to fill voids over properly prepared existing cement terrazzo, ceramic tile, VCT, or non-cushioned, fully adhered residential sheet vinyl flooring, cutback and carpet adhesive residues.

FEATURES AND BENEFITS

- For use on concrete and plywood substrates
- Levels and smooths substrates prior to the installation of floor covering
- Ideal for patching and leveling from 1/16" to 1/2"
- Easy to prepare and quick to apply
- Fast drying, foot traffic in 30 to 60 minutes
- Repairs new and renovate old floors
- Apply over properly prepared cutback, embossed resilient vinyl floors and existing ceramic tile
- For use with SikaBond[®] adhesives with solid and engineered hardwood
- Excellent standard of finish can be achieved to allow direct application of coverings
- Mold and mildew resistant

NOTE: Always refer to Current Product data Sheet and SDS for detailed performance specifications prior to use.

TYPICAL DATA - MATERIAL AND CURING CONDITIONS @ 73°F (23°C) AND 50% R.H.

Application Thickness	1/16" - 1/2"
Working Time	10 - 20 Minutes
Setting Times	Initial: 20 - 30 Minutes Final: 60 - 90 Minutes
VOC	0 g/L

APPROXIMATE COVERAGE

THICKNESS	COVERAGE PER BAG
1/16"	50-60 sqft. (4.6 m2)
1/8"	25-30 sqft (2.3 m2)
1/4"	12.5-15 sqft. (1.2 m2)
1/2"	6-7.5 sqft. (0.6 m2)



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.SikaSecure.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225

BUILDING TRUST

