



Sika[®] Concrete Primer Lo-VOC

**COLD APPLIED, MOISTURE-CURING POLYURETHANE RESIN.
DESIGNED AS PART OF SIKALASTIC[®] ROOFPRO SYSTEMS.**

- Fast curing formulation - cures within 45 minutes
- Single component, easy to apply
- Compatible with most concrete, masonry, and stone substrate materials
- No Mixing Required

Available in
Pail
5 gal



BUILDING TRUST



Sika[®] Concrete Primer Lo-VOC

SINGLE COMPONENT POLYURETHANE PRIMER

WHERE TO USE

Suitable for use on most sound substrate surfaces where both a penetrative and surface-lying effect is required. Use on concrete, concrete block, cement board, hardboard, plywood, brick.

MAIN ADVANTAGES

- Can be applied over sealants
- In 45 minutes tack-free
- Vertical or horizontal
- No mixing, easy to split into smaller pails

TYPICAL DATA

- VOC Content: < 95 g/L
- Cure Time: 30-45 minutes at 77°F & 50% RH
- Recoat Time: Up to 72 hours
- Bond Strength (ACI 503R, Appendix A): > 400 psi concrete



FOR MORE INFORMATION:

Contact Sika: Phone 800.933.SIKA(7452) Website: www.sikausa.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225



BUILDING TRUST

