



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

SECTION 1. IDENTIFICATION

Product name : Sikafloor® 510 LPL Part A

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 2

Specific target organ toxicity : Category 2
- repeated exposure (Inhalation)

Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

GHS label elements



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H351 Suspected of causing cancer if inhaled.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

Supplemental Hazard Statements :

Corrosive to the respiratory tract.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

| Chemical name | CAS No./Unique ID | Classification | Concentration (% w/w) |
|----------------------------------------------------------------------------|-------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane | 136210-32-7 | Skin Sens. 1; H317 | $\geq 15 - \leq 40$ |
| Isophorondiamine-Isobutyraldimine | 54914-37-3 | Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 | $\geq 5 - \leq 10$ |
| Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediy)bis-, tetraethyl ester | 136210-30-5 | Skin Sens. 1; H317 | $\geq 3 - \leq 7$ |
| xylene | 1330-20-7 | Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304 | $\geq 3 - \leq 7$ |
| diethyl maleate | 141-05-9 | Skin Sens. 1; H317 | $\geq 1 - \leq 5$ |
| Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics | 64742-47-8 | Asp. Tox. 1; H304 | $\geq 0.5 - \leq 1.5$ |
| ethylbenzene | 100-41-4 | Flam. Liq. 2; H225 Acute Tox. 4; H332 Carc. 2; H351 STOT RE 2; H373 Asp. Tox. 1; H304 Eye Irrit. 2A; H319 | $\geq 0.1 - \leq 1$ |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

- If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
Suspected of causing cancer if inhaled.
May cause damage to organs through prolonged or repeated exposure if inhaled.
Corrosive to the respiratory tract.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency measures : Use personal protective equipment.
Deny access to unprotected persons.



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

gency procedures

Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|-----------|-------------------------------|------------------------------------------------|----------|
| xylene | 1330-20-7 | TWA | 100 ppm 435 mg/m ³ | OSHA Z-1 |
| | | TWA | 20 ppm | ACGIH |
| | | STEL | 150 ppm | OSHA P0 |



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

| | | | | |
|--------------|----------|------|----------------------|----------|
| | | | 655 mg/m3 | |
| | | TWA | 100 ppm 435 mg/m3 | OSHA P0 |
| ethylbenzene | 100-41-4 | TWA | 100 ppm 435 mg/m3 | OSHA Z-1 |
| | | TWA | 100 ppm 435 mg/m3 | OSHA P0 |
| | | STEL | 125 ppm 545 mg/m3 | OSHA P0 |
| | | TWA | 20 ppm | ACGIH |

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.
 Wash hands before breaks and immediately after handling the product.
 Remove contaminated clothing and protective equipment before entering eating areas.
 Wash thoroughly after handling.



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--------------------------------------------------|---|--------------------------------------------------|
| Appearance | : | liquid |
| Color | : | light yellow |
| Odor | : | amine-like |
| Odor Threshold | : | No data available |
| pH | : | Not applicable |
| Melting point/ range / Freezing point | : | No data available |
| Boiling point/boiling range | : | No data available |
| Flash point | : | > 199.99 °F / > 93.33 °C (Method: closed cup) |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapor pressure | : | 0.01 hpa |
| Relative vapor density | : | No data available |
| Density | : | ca. 1.03 g/cm ³ (73 °F / 23 °C) |
| Solubility(ies) | | |
| Water solubility | : | partly soluble |
| Solubility in other solvents | : | No data available |
| Partition coefficient: n-octanol/water | : | No data available |
| Autoignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | | |
| Viscosity, dynamic | : | No data available |



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

| | | |
|------------------------------------------|---|--------------------------------------------|
| Viscosity, kinematic | : | > 20.5 mm ² /s (104 °F / 40 °C) |
| Explosive properties | : | No data available |
| Oxidizing properties | : | No data available |
| Volatile organic compounds (VOC) content | : | 92 g/l A+B Combined |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|-------------------------------------------------------------|
| Reactivity | : | No dangerous reaction known under conditions of normal use. |
| Chemical stability | : | The product is chemically stable. |
| Possibility of hazardous reactions | : | Stable under recommended storage conditions. |
| Conditions to avoid | : | No data available |
| Incompatible materials | : | No data available |
| Hazardous decomposition products | : | No decomposition if stored and applied as directed. |

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

Isophorondiamine-Isobutyraldimine:

Acute oral toxicity : LD50 Oral (Rat): 4,150 mg/kg

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3,523 mg/kg

diethyl maleate:

Acute oral toxicity : LD50 Oral (Rat): 3,200 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 5,000 mg/kg

Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

ethylbenzene:

Acute oral toxicity : LD50 Oral (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 5,510 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Method : In Vitro Membrane Barrier Test Method for Skin Corrosion -
CORROSITEX

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer if inhaled.

IARC Group 2B: Possibly carcinogenic to humans
ethylbenzene 100-41-4

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

Corrosive to the respiratory tract.



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if inhaled.
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

xylene:

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): > 1.3 mg/l
Exposure time: 56 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia): 1.17 mg/l
Exposure time: 7 d

diethyl maleate:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 53 mg/l
Exposure time: 48 h

Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR Road

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

| Components | CAS-No. | Component RQ (lbs) |
|------------|-----------|--------------------|
| xylene | 1330-20-7 | 100 |

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

SARA 311/312 Hazards : Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

xylene 1330-20-7 >= 1 - < 5 %

ethylbenzene 100-41-4 >= 0.1 - < 1 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

xylene 1330-20-7 >= 1 - < 5 %

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including ethylbenzene, which is known to the State of California to cause cancer, and toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA : 8-hour, time-weighted average
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.



Sikafloor® 510 LPL Part A

Revision Date 03/19/2025

Print Date 03/19/2025

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 03/19/2025

000000606714
US / Z8