

## PRODUCT DATA SHEET

# Sarnatherm<sup>®</sup> Roof Board M

SARNATHERM ROOF BOARD M IS A HIGH-DENSITY POLYISOCYANURATE ROOF BOARD

### PRODUCT DESCRIPTION

Sarnatherm<sup>®</sup> Roof Board M is a lightweight, high-density polyisocyanurate roof board with coated glass facers. Sarnatherm<sup>®</sup> Roof Board M is suitable for use in new construction and recover roof applications with Sarnafil<sup>®</sup> or Sikaplan<sup>®</sup> roof membranes. The coated glass facers provide strong, smooth surfaces suitable for mechanically attached or adhered applications.

### USES

Used as a lightweight roof board in conventional roof assemblies

#### Areas of Application

- New Roofs
- Recover Roofs
- Mechanically Attached Systems
- Adhered Systems

### CHARACTERISTICS / ADVANTAGES

- Lightweight for easy hoisting, staging and maneuvering
- High impact and flexural strength
- Easy scoring, cutting and snapping
- Improved coverage rates in adhered systems

### APPROVALS / STANDARDS

- ASTM C1289, Type II, Class 4, Grades 1, 2, & 3
- FM 4450 / 4470
- UL Classified 790
- Miami-Dade County

## PRODUCT INFORMATION

<b>Chemical Base</b>	Polyisocyanurate foam core with coated glass facers.
<b>Recycled Content</b>	3.7% Pre-consumer
<b>Packaging</b>	4 ft x 4 ft (1.2 m x 1.2 m), 6 lbs (2.72 kg) 4 ft x 8 ft (1.2 m x 2.4 m), 12 lbs (5.4 kg) 0.25" (6.4 mm) thickness, 30 boards per pallet
<b>Color</b>	Off-white core with off white/light tan facers
<b>Shelf Life</b>	N/A
<b>Storage Conditions</b>	Factory-applied packaging is intended only for protection during transit. When stored outdoors or on the job site, the insulation should be stacked on pallets at least 4" (102 mm) above ground level and completely covered with a weatherproof covering such as a tarpaulin. The temporary factory-applied packaging should be slit or removed to prevent accumulation of condensation. Refer to PIMA Technical Bulletin #109: <i>Storage and Handling Recommendations for Polyiso Roof Insulation</i> .

## TECHNICAL INFORMATION

<b>Compressive Strength</b>	150 psi (1,034 kPa)	(ASTM D-1621)
<b>Flexural Strength</b>	1500 psi (10,343 kPa) <sup>1</sup> 25 lbf (0.111 kN) <sup>2</sup>	(ASTM D-1037)
	<sup>1</sup> Modulus of Rupture, <sup>2</sup> Breakload	
<b>Dimensional Stability</b>	< 1 %	(ASTM D-2126)
<b>Thermal Resistance</b>	1.2	(ASTM C-518)
<b>Permeability to Water Vapor</b>	< 1 Perm (< 57.5 ng/(Pa·s·m <sup>2</sup> ))	(ASTM E-96)
<b>Water Absorption</b>	< 4 %	(ASTM C-209)
<b>Microbiological Resistance</b>	Pass	(ASTM D-3273)

## APPLICATION INSTRUCTIONS

Sarnatherm® Roof Board M is installed by a Sika Authorized Applicator. Sarnatherm® Roof Board M may be installed by mechanical attachment to the roof deck with approved fasteners and insulation plates or by attachment with Sarnacol board adhesive depending on project requirements and specifications. Roof boards that have become wet or damaged should be removed and replaced with solid, dry roof boards. Contact Sika Corporation – Roofing Technical Department regarding alternative methods of attachment.

## MAINTENANCE

Standard maintenance of Sarnafil® or Sikaplan® systems should include regular inspection of flashings, drains and termination sealants at least twice a year and after each storm.

## AVAILABILITY/WARRANTY

### Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

### Warranty

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

**Sika Corporation**  
201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Sarnafil**  
100 Dan Road  
Canton, MA 02021  
Phone: +1 800-451-2504  
Fax: +1 781-828-5365  
[usa.sarnafil.sika.com](http://usa.sarnafil.sika.com)  
[webmaster.sarnafil@us.sika.com](mailto:webmaster.sarnafil@us.sika.com)

**Sika Mexicana S.A. de C.V.**  
Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



Product Data Sheet  
Sarnatherm® Roof Board M  
September 2019, Version 03.01  
020935013000005010

SarnathermRoofBoardM-en-US-(09-2019)-3-1.pdf

