

PRODUCT DATA SHEET

SikaCem®-100 Flattening Paste

Solvent-based silica paste for use in SikaCem® solvent-based sealers to reduce the surface gloss of the dried film these sealers create

PRODUCT DESCRIPTION

SikaCem®-100 Flattening Paste is a solvent-based silica paste added directly to SikaCem® solvent-based sealers to reduce the surface gloss of the dried film these sealers create. Previously named Butterfield Color® Flattening Paste.

USES

- Added directly to SikaCem®-100 Clear Guard®, SikaCem®-100 PRO 350®, SikaCem®-100 Silane PRO 350®, and SikaCem®-100 PRO 100 to reduce the surface gloss of the dried film these solvent-based sealers create

CHARACTERISTICS / ADVANTAGES

- Reduces surface gloss of the sealer

PRODUCT INFORMATION

Chemical Base	Solvent-Based
Packaging	1 qt. (0.9 L) fill in 1 qt. (0.9 L) steel can
Shelf Life	36 months in original unopened container
Storage Conditions	Store in original, unopened containers in dry storage.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding

APPLICATION INSTRUCTIONS

MIXING

Add the entire 1 qt. (0.9 L) container to 5 gal. (18.9 L) of SikaCem® solvent-based sealer being used. Do not thin or alter with any chemical. Mix thoroughly with a drill-mounted mixer. Do not introduce air bubbles by excessive high-speed mixing. Remix periodically.

APPLICATION

Once SikaCem®-100 Flattening Paste is mixed into the SikaCem® solvent-based sealer being used, consult the most current SikaCem® solvent-based sealer being used local Product Data Sheet for complete Application Instructions.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
SikaCem®-100 Flattening Paste
June 2026, Version 02.02
021405071000000110

SikaCem-100FlatteningPaste-en-US-(06-2026)-2-2.pdf

