

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

SECTION 1. IDENTIFICATION

Product name : Sikalastic M 205 SL Formerly MSeal M 205 SL
Product code : 000000000050465381
Other means of identification : MSeal M 205 SL

Manufacturer or supplier's details

Company name of supplier : Sika MBCC US LLC
Address : 201 POLITO AVE
Lyndhurst NJ 07071
Emergency telephone : ChemTel: +1-813-248-0585
National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Water repellent
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3
Acute toxicity (Inhalation) : Category 4
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Carcinogenicity : Category 2
Reproductive toxicity : Category 1B
Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Central nervous system)
Short-term (acute) aquatic hazard : Category 3

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version 4.0 Revision Date: 06/16/2025 SDS Number: 000000722889 Date of last issue: 06/13/2025
Date of first issue: 07/09/2020

Other hazards

Contains isocyanates. Inhalation of isocyanate mists or vapors may cause respiratory irritation, breathlessness, chest discomfort and reduced pulmonary function. Overexposure well above the PEL may result in bronchitis, bronchial spasms and pulmonary edema. Animal tests indicate that skin contact may play a role in causing respiratory sensitization.

GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapor.
H317 May cause an allergic skin reaction.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H351 Suspected of causing cancer.
H360 May damage fertility or the unborn child.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
H402 Harmful to aquatic life.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.
P280 Wear protective gloves, protective clothing, eye protection and face protection.
P285 In case of inadequate ventilation wear respiratory protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version 4.0 Revision Date: 06/16/2025 SDS Number: 000000722889 Date of last issue: 06/13/2025
Date of first issue: 07/09/2020

all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : polyurethane

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Limestone	1317-65-3*	>= 10 - <= 30	TSC
talc	14807-96-6*	>= 5 - <= 10	TSC
4-Chloro- α,α,α -trifluorotoluene	98-56-6*	>= 3 - <= 7	TSC
Stoddard solvent	8052-41-3*	>= 3 - <= 7	TSC
Calcium sulphate	7778-18-9*	>= 1 - <= 5	TSC
Titanium dioxide	13463-67-7*	>= 0.5 - <= 1.5	TSC
toluene-2,6-diisocyanate	91-08-7*	>= 0.1 - <= 1	TSC
4-methyl-m-phenylene diisocyanate	584-84-9*	>= 0.1 - <= 1	TSC
dibutyltin dilaurate	77-58-7*	>= 0.1 - <= 1	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

SECTION 4. FIRST AID MEASURES

- General advice : Remove contaminated clothing.
- If inhaled : Remove the affected individual into fresh air and keep the person calm.
Assist in breathing if necessary.
Immediate medical attention required.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
If irritation develops, seek medical attention.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Remove contact lenses, if present.
Seek medical advice.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.
Do NOT induce vomiting.
Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.
Immediate medical attention required.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Suspected of causing cancer.
May damage fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Dry powder
Carbon dioxide (CO₂)
Foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Reacts with water, with formation of carbon dioxide.
- Hazardous combustion products : nitrous gases
fumes/smoke
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

isocyanate
vapor

Further information : If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Do not breathe vapour/aerosol/spray mists.
Wear respiratory protection.
Wear eye/face protection.
Use personal protective clothing.
If exposed to high vapour concentration, leave area immediately.
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
Dispose of in accordance with national, state and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Open drum carefully as content may be under pressure.
Persons susceptible to skin sensitization problems or asthma,

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Ensure thorough ventilation of stores and work areas.
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.
Wear respiratory protection when spraying.
Danger of bursting when sealed gastight.
Protect against moisture.

Conditions for safe storage : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Prevent unauthorized access.

Further information on storage stability : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total dust)	15 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
		TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m ³	OSHA P0
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable par-	2 mg/m ³	ACGIH

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version 4.0 Revision Date: 06/16/2025 SDS Number: 000000722889 Date of last issue: 06/13/2025
 Date of first issue: 07/09/2020

		ticulate matter)		
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
Calcium sulphate	7778-18-9	TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhalable particulate matter)	10 mg/m3 (Calcium)	ACGIH
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.2 mg/m3 (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m3 (Titanium dioxide)	ACGIH
toluene-2,6-diisocyanate	91-08-7	C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
4-methyl-m-phenylene diisocyanate	584-84-9	C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	0.001 ppm	ACGIH

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version 4.0 Revision Date: 06/16/2025 SDS Number: 000000722889 Date of last issue: 06/13/2025
Date of first issue: 07/09/2020

		and vapor)		
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m ³	OSHA P0
		STEL	0.02 ppm 0.15 mg/m ³	OSHA P0
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m ³ (Tin)	OSHA Z-1
		TWA	0.1 mg/m ³ (Tin)	ACGIH
		STEL	0.2 mg/m ³ (Tin)	ACGIH
		TWA	0.1 mg/m ³ (Tin)	OSHA P0
		TWA	0.1 mg/m ³ (Tin)	NIOSH REL

Engineering measures : Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber fluoroelastomer (Viton) depending upon conditions of use. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.
Wear face shield if splashing hazard exists.

Skin and body protection : Cover as much of the exposed skin as possible to prevent all skin contact.
Suitable materials may include saran-coated material
Chemical resistant protective boots
depending upon conditions of use.

Protective measures : Do not inhale gases/vapours/aerosols.
Observe the appropriate PEL or TLV value.
Wear protective clothing as necessary to prevent contact.
Eye wash fountains and safety showers must be easily ac-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

cessible.

Hygiene measures : Avoid contact with skin, eyes and clothing.
No eating, drinking, smoking or tobacco use at the place of work.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Hands and/or face should be washed before breaks and at the end of the shift.
Wash soiled clothing immediately.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: gray
Odor	: aromatic, solvent
Odor Threshold	: not determined
pH	: No data available
Melting point/freezing point	: No data available
Boiling range	: 428 - 572 °F / 220 - 300 °C
Flash point	: 120 - 127 °F / 49 - 53 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data available
Flammability (liquids)	: Flammable liquid and vapor.
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: No data available
Density	: approx. 1.25 g/cm ³ (68 °F / 20 °C)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

Solubility(ies)
Water solubility : slightly soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : Not applicable

Autoignition temperature : not determined

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Sublimation point : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : Reacts with water, with formation of carbon dioxide.
Risk of bursting.
Reacts with alcohols.
Reacts with acids.
Reacts with alkalis.
Reacts with amines.
Risk of exothermic reaction.
Risk of polymerization.
Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.
Vapors may form explosive mixture with air.

Conditions to avoid : Avoid all sources of ignition: heat, sparks, open flame.
Avoid moisture.

Incompatible materials : Acids

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

Amines
Alcohols
Water
Alkalines
Strong bases
Substances/products that react with isocyanates.

Hazardous decomposition products : nitrogen oxides
Aromatic isocyanates
gases/vapours

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if inhaled.

Product:

Acute inhalation toxicity : Acute toxicity estimate: 10.17 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Skin corrosion/irritation

Not classified due to lack of data.

Serious eye damage/eye irritation

Not classified due to lack of data.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Suspected of causing cancer.

IARC	Group 2B: Possibly carcinogenic to humans 4-Chloro- α,α,α -trifluorotoluene	98-56-6
	Group 2B: Possibly carcinogenic to humans Titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans toluene-2,6-diisocyanate (toluene diisocyanates)	91-08-7
	Group 2B: Possibly carcinogenic to humans 4-methyl-m-phenylene diisocyanate (toluene diisocyanates)	584-84-9
NTP	Reasonably anticipated to be a human carcinogen toluene-2,6-diisocyanate	91-08-7

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

Reasonably anticipated to be a human carcinogen
4-methyl-m-phenylene diisocyanate 584-84-9

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Incinerate or dispose of in a licensed facility.
Dispose of isocyanate waste in dry containers and never mix together with other wastes (reaction, dangerous pressure build up).
Do not discharge substance/product into sewer system.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.
-

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

- UN number : UN 1263
Proper shipping name : PAINT
Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : no

IATA-DGR

- UN/ID No. : UN 1263
Proper shipping name : Paint
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

- UN number : UN 1263
Proper shipping name : PAINT
- Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

- UN/ID/NA number : UN 1263
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version 4.0 Revision Date: 06/16/2025 SDS Number: 000000722889 Date of last issue: 06/13/2025
Date of first issue: 07/09/2020

Proper shipping name : PAINT

Class : C
Packing group : III
Labels : Combustible Liquid
ERG Code : 128
Marine pollutant : no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene-2,6-diisocyanate	91-08-7	100	10548

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene-2,6-diisocyanate	91-08-7	>= 0.1 - < 1 %
4-methyl-m-phenylene diisocyanate	584-84-9	>= 0.1 - < 1 %

US State Regulations

Pennsylvania Right To Know

Limestone	1317-65-3
talc	14807-96-6
Stoddard solvent	8052-41-3
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
toluene-2,6-diisocyanate	91-08-7
4-methyl-m-phenylene diisocyanate	584-84-9

New Jersey Right To Know

Limestone	1317-65-3
talc	14807-96-6
4-Chloro- α,α,α -trifluorotoluene	98-56-6
Stoddard solvent	8052-41-3
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
toluene-2,6-diisocyanate	91-08-7
4-methyl-m-phenylene diisocyanate	584-84-9

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version 4.0 Revision Date: 06/16/2025 SDS Number: 000000722889 Date of last issue: 06/13/2025
Date of first issue: 07/09/2020

California Prop. 65

WARNING: This product can expose you to chemicals including 4-Chloro- α,α,α -trifluorotoluene, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:

toluene-2,6-diisocyanate	91-08-7	See 40 CFR § 721.10789; Proposed Rule Proposed Rule
4-methyl-m-phenylene diisocyanate	584-84-9	See 40 CFR § 721.10789; Proposed Rule Proposed Rule


The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

toluene-2,6-diisocyanate	91-08-7
4-methyl-m-phenylene diisocyanate	584-84-9

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-1 / C	:	Ceiling
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

BASF CORPORATION WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Sikalastic M 205 SL Formerly MSeal M 205 SL

Version	Revision Date:	SDS Number:	Date of last issue: 06/13/2025
4.0	06/16/2025	000000722889	Date of first issue: 07/09/2020

PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.

Revision Date : 06/16/2025

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN