



PRODUCT DATA SHEET

Sikafloor®-101 AC Pronto

(formerly MTop SRS 101AC)

METHYL-METHACRYLATE COLD TEMPERATURE ADDITIVE

PRODUCT DESCRIPTION

The careful addition of Sikafloor®-101 AC Pronto at jobsite mix stations allows for application of certain Sikafloor® Pronto products at below specified temperatures, down to -20°F. Sikafloor®-101 AC Pronto is always added to the resin and mixed thoroughly before the addition of Sikafloor®-100 HD Pronto powder hardener.

USES

- Below 32°F (0°C) application
- Enhances bond promotion to metal surfaces when used with Sikafloor®-102 AP Pronto

CHARACTERISTICS / ADVANTAGES

- Assists the low temperature hardening of Sikafloor® Pronto reactive resins when added to the mix prior to adding Sikafloor®-100 HD Pronto

PRODUCT INFORMATION

Packaging	32 oz container
Shelf Life	48 months
Storage Conditions	Sikafloor®-101 AC Pronto must never come into direct contact with Sikafloor®-100 HD Pronto hardening powder, as otherwise an uncontrollable explosion may occur. Sikafloor®-101 AC Pronto and Sikafloor®-100 HD Pronto must be stored and staged separately. Store in original, unopened container, in cool dry storage, away from heat and direct sunlight

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
Sikafloor®-101 AC Pronto
May 2025, Version 05.01
020816220010000033

Sikafloor-101ACPronto-en-US-(05-2025)-5-1.pdf

