



CASE STUDY

MARKET APPLICATION FOCUS

Parking

Waterproofing

Crackbridging Deck Membrane

Project: Cathedral Hill Project
San Francisco, CA
Specifier: Clark & Wilkins
Contractor: Alpha Restoration & Waterproofing
Year: 1998

THE PROBLEM



A failed waterproofing membrane caused moisture to leak into and become trapped between the layers of a split-slab concrete plaza deck. The options for the owner were to remove the concrete topping slab and replace the waterproofing layer on the structural slab or find a way to waterproof on top of the topping slab. After taking readings of MVT (Moisture Vapor Transmission) it was determined that direct application of the Sikafloor Traffic System was not an option. Calcium Chloride tests showed transmission of 6 to 13 pounds of water over 1,000 square feet in 24 hours (industry standards allow only 3 pounds or less).

THE SIKA SOLUTION

To place the resinous Sikafloor Traffic System, an "osmotic buffer" would first need to be installed. This is not an option in freeze/thaw climates, however the mild climate of San Francisco made the use of Sikafloor EpoCem 81 an excellent option.

After removal of the existing waterproofing layer the concrete was prepared using Blastrac[®] shotblasting equipment. Alpha Restoration then installed the Sikafloor EpoCem 81. This unique combination of epoxy and cement in the EpoCem 81 allowed the contractor to use a self-leveling mortar to temporarily stop the MVT. Once the MVT was stopped with the EpoCem, installation of the Sikafloor Traffic System proceeded.



After the sealant was installed in the cracks and joints the deck was primed using Sikafloor 152 primer, a two-component solvent containing epoxy primer. The waterproofing layer was then installed using Sikafloor 450, a single-component, moisture-cured urethane. The Pedestrian Duty Traffic System was then completed using one coat of Sikafloor 455, Sika's UV stable, extremely abrasion resistant, single-component top coat.



For Parking Garages... Sika's System approach to Concrete Repair and Protection

Corrosion Inhibitors

Sika FerroGard® 903 as a dual action, corrosion inhibitor will reduce corrosion currents by penetrating through the concrete and forming a protective coating on the embedded steel bars.

Anti-Corrosion Primer and Bonding Bridge

Sika Armatec® 110 Epocem protects the steel from corrosion in areas of inadequate cover. Improves bond of repair mortar to both substrate and steel.

High Performance Repair Mortars

Sikatop® Plus Mortars - two component polymer modified materials containing Sika Ferrogard 901 corrosion inhibiting admixture.

Sikacem® mortars are machine applied by dry process shotcrete techniques for large scale repair.

Problem Joints/Crack Sealing

Sikadur® Combiflex is a unique 'strip and seal' system used to seal irregular or large cracks, even those having large or shear movement.

Crackbridging Deck Membrane

Sikafloor® 450/455 is a single component polyurethane system used in locations from aggressive vehicular abrasion to foot traffic of balconies and plaza decks.

Epoxy Injection and Bonding

Sikadur® epoxy resins help restore structural integrity by injection of cracks and voids.

Structural Strengthening Systems CFRP

Sika CarboDur® a proven system of external strengthening using epoxy bonded lightweight carbon Fiber Reinforced Polymer (CFRP) strips or sheet. Stronger than steel yet lightweight and non corrosive, this strengthening system can solve unique strengthening systems in many concrete structures.

Anti-Carbonation Coatings

Sikagard® Facade Coatings have been proven for more than 20 years as protective and decorative coatings for facades and soffits to prevent the ingress of water, carbon dioxide (carbonation) but will still allow the structure to breathe and move thermally and dynamically.

1-800-933-SIKA NATIONWIDE

Regional Headquarters and Sales Centers

For the location of your nearest Sika sales office, contact your regional center.



Sika Corporation (USA)
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Corregidora, Queretaro
C.P. 76920 A.P. 136
Phone: 52 42 25 0122
Fax: 52 42 25 0537

Sika Canada, Inc.
601 Delmar Avenue
Pointe Claire,
Quebec H9R4A9
Phone: 514-697-2610
Fax: 514-694-2792

The information contained in this document(s), including but not limited to any recommendations regarding the use and application of Sika Corporation ("Sika") product(s), is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. The information contained in this document(s) is valid only for the applications and uses of Sika product(s) described herein. Any deviation from any of the instructions, uses, applications and recommendations contained in this document(s) regarding the Sika product(s) will void any Sika warranty. The user of the Sika product(s) must test each product for suitability for the intended application and purpose. The user of Sika product(s) must always read and follow the warnings and instructions for each product on the current Technical Data Sheet, product label and Material Safety Data Sheets prior to product use. All sales of Sika product(s) are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800. Technical Data Sheet(s) and Material Safety Data Sheet(s) are available at www.sikaconstruction.com. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instructions for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet. Sale of Sika product(s) are subject to the following Limited Material Warranty: Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

SIKA...A SYMBOL OF STRENGTH SINCE 1910