



CASE STUDY

MARKET APPLICATION FOCUS

Buildings

Waterproofing

Sealants

Project: The Port Authority of New York and New Jersey
Owner: State of New York
Architect: Albert Brevetti
Construction: Crest Construction
Contractor: Arrow Building Restoration
Year: 1978

THE PROBLEM

The New York State Capitol building has been a prominent and impressive structure in Albany since 1897, when it was first constructed. Since its opening, the building was burdened with cracks in the ceiling of the assembly hall, settlement due to a bed of glacial clay and leaking into the interior of the building. The leaks continued due to careless and spotty sealing with ineffective materials. When the decision to restore the building was finally made, it was important the building would be leak free. Because the building was very important to the City of Albany, aesthetics were also a concern. Plus the amount of joint sealing that would be required meant that the product chosen to seal all the joints would be very visible.



THE SIKA SOLUTION

A full-scale analysis was completed to determine the cause of leaking throughout the building structure. The conclusion of the examination was that poor quality materials and workmanship were the root cause. The group assembled to conduct the repair approach required the sealant meet several criteria: handle joint movement, tenacious bond, handle harsh weather exposure and ease of application. Also, the many different substrates were evaluated to select a mutually compatible sealant. Sikaflex 1a, one-component polyurethane sealant, was chosen for its ability to meet all the demands of the building owner. Additional benefits realized by the contractor were primerless application, non-staining and a paintable surface.

The building restoration was completed and the project was inspected almost 20 years later and remained leak-free. Less than 2% of the half million feet of original sealing needed touch-up. The project was a success.





For Structures... Sika's System approach to Concrete Repair and Protection

Anti-Corrosion Primer and Bonding Bridge

Sika Armatec® 110 EpoCem® - protects the steel from corrosion in areas of inadequate cover. Improves bond of repair mortar to both substrate and steel.

High Performance Repair Mortars

SikaTop® Plus mortars - two component polymer modified materials containing Sika FerroGard 901 corrosion-inhibiting admixture.

Corrosion-Inhibiting Impregnation

Sika FerroGard® 903 - spray-applied to protect areas outside the repair zone against future damage. Proven to penetrate and reduce corrosion effects of carbonation and salt exposure.

Surface Leveling/Pore-Filling Mortars

SikaTop® leveling mortars - achieve a level surface by filling pores, bugholes, or other irregularities in the surrounding substrate.

Anti-Carbonation Coatings

Sikagard® 550W and 670W - protect concrete facades from the damaging effects of carbon dioxide (carbonation), water and pollutants. Either crack-bridging (550W) or rigid (670W), both are available in a variety of decorative colors.

Joint Sealing/Waterproofing


Sikaflex® High Performance Sealants - premium-grade polyurethane joint sealants that are fully compatible with Sika's concrete repair systems.

Epoxy Injection and Bonding

Sikadur® epoxy resins help restore structural integrity by injection of cracks and voids. The most comprehensive range of epoxy products for structural bonding and grouting.

Structural Strengthening Systems (FRP)

Sika CarboDur® & SikaWrap® - a proven system of external strengthening using carbon fiber laminate strips, carbon fiber fabric, and glass fiber fabric. Stronger than steel yet lightweight and non-corrosive, these system components can solve unique strengthening problems in a variety of concrete structures.



1-800-933-SIKA NATIONWIDE

Regional Headquarters and Sales Centers

For the location of your nearest Sika sales office, contact your regional center.



Responsible Care®
Good Chemistry at Work



Sika Corporation (USA)
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Corregidora, Queretaro
C.P. 76920 A.P. 136
Phone: 52 42 25 0122
Fax: 52 42 25 0537

Sika Canada, Inc.
601 Delmar Avenue
Pointe Claire,
Quebec H9R4A9
Phone: 514-697-2610
Fax: 514-694-2792

The information contained in this document(s), including but not limited to any recommendations regarding the use and application of Sika Corporation ("Sika") product(s), is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. The information contained in this document(s) is valid only for the applications and uses of Sika product(s) described herein. Any deviation from any of the instructions, uses, applications and recommendations contained in this document(s) regarding the Sika product(s) will void any Sika warranty. The user of the Sika product(s) must test each product for suitability for the intended application and purpose. The user of Sika product(s) must always read and follow the warnings and instructions for each product on the current Technical Data Sheet, product label and Material Safety Data Sheets prior to product use. All sales of Sika product(s) are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800. Technical Data Sheet(s) and Material Safety Data Sheet(s) are available at www.sikaconstruction.com. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instructions for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet. Sale of Sika product(s) are subject to the following Limited Material Warranty: Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.