

## PRODUCT DATA SHEET

# Greenstreak® PVC Waterstop

### Flexible PVC Waterstop

#### PRODUCT DESCRIPTION

Greenstreak® PVC Waterstop is a flexible PVC waterstop for joint waterproofing.

#### USES

- Water/Waste Water Treatment Plants
- Lock and Dam Systems
- Reservoirs and Aqueducts
- Flood Walls
- Retaining Walls
- Foundations
- Tunnels and Culverts
- Bridge Abutments
- Containment Structures and Tanks
- Slabs-on-Ground

#### CHARACTERISTICS / ADVANTAGES

- Embedded in concrete, across and/or along the joint, waterstops form a watertight diaphragm that prevents the passage of liquid through the joint.
- Suitable for potable water contact, meets NSF/ANSI Standard 61.
- Meets the physical property requirements of Army Corp. of Engineers PVC Waterstop Specification CRD-C 572-74

#### PRODUCT INFORMATION

<b>Packaging</b>	Available in various lengths.
<b>Shelf Life</b>	N/A
<b>Storage Conditions</b>	Material must be protected from direct sunlight

#### TECHNICAL INFORMATION

Product Data Sheet  
Greenstreak® PVC Waterstop  
November 2019, Version 01.02  
020703100100000113

Shore A Hardness	79 +/- 3	(ASTM D2240)
Tensile Strength	2000 psi min.	(ASTM D638)
Elongation	350%	(ASTM D638)
Tear Strength	300 lb/in min	(ASTM D624)
Ambient Air Temperature	Low Temperature Brittleness Passes at -35°F (-37°C)	(ASTM D746)

## APPLICATION INSTRUCTIONS

### APPLICATION METHOD / TOOLS

Greenstreak® PVC Waterstop must be installed prior to concrete placement to ensure proper positioning and concrete consolidation around the waterstop. All transitions, intersections, and splices should be heat welded to maintain continuity. Factory Made Fabrications are recommended for all intersections and changes of direction. Specific installation requirements will vary depending on the style of profile, please refer to Sika's PVC Waterstop Installation Guide and Splicing PVC Waterstop Installation Guide available at [usa.sika.com](http://usa.sika.com). All transitions, intersections, and splices must be heat welded using a Sika Greenstreak Splicing Iron in compliance with the instructions shown in Sika's Splicing PVC Waterstop Installation Guidelines found at [usa.sika.com](http://usa.sika.com).

### LIMITATIONS

The size, shape, and style of waterstop should be based on specific application needs. Please consult a Sika Greenstreak Engineer at 800-325-9504 for assistance with profile selection.

### BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

### OTHER RESTRICTIONS

See Legal Disclaimer.

## ENVIRONMENTAL, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

### LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS**

**PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT  
OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD  
BY OTHERS.**

Sale of SIKA products are subject to the Terms and  
Conditions of Sale which are available at  
<https://usa.sika.com/en/group/SikaCorp/termsandconditions.html>  
or by calling 1-800-933-7452.

**Sika Corporation**

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

**Sika Mexicana S.A. de C.V.**

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



**Product Data Sheet**

Greenstreak® PVC Waterstop  
November 2019, Version 01.02  
020703100100000113

GreenstreakPVCWaterstop-en-US-(11-2019)-1-2.pdf

