

Sikafloor® Comfort Regupol 6015H

Rubber shockpad part of the Sikafloor ComfortFloor Pro

Description	Sikafloor Comfort Regupol 6015H is a prefabricated rubber shockpad produced by bonding rubber crumb with a polyurethane compound.
Where to Use	<ul style="list-style-type: none">■ Hospitals■ Educational Facilities■ Stores (Retail, Grocery, Specialty)■ Showrooms■ Lobbies■ Office spaces■ Museums and theaters■ For interior use only
Advantages	<ul style="list-style-type: none">■ Flexible■ Shock and sound absorption■ High impact resistance■ Durable, high quality shockpad
Chemical Resistance	Sikafloor Comfort Regupol 6015 must be overcoated, consult chemical resistance guide of Sikafloor Comfort Floor selected topcoat. (Sikafloor 304 W, Sikafloor 305 W) Visit www.sikafloorusa.com or contact Sika Technical Service at 800-933-SIKA
How To Use	
Surface Preparation	Substrate Quality Concrete substrates must be sound and of sufficient compressive strength 3,625 psi (minimum 25 N/mm ²) with a minimum pull off strength of 217 psi (1.5 N/mm ²). The substrate must be clean, dry and free of all contaminants such as dirt, oil, grease, coatings and surface treatments, etc. If in doubt, apply a test area first. Concrete substrates and cementitious screeds must be prepared mechanically using abrasive blast cleaning or scarifying equipment to remove cement laitance and achieve an open textured surface. Weak concrete must be removed and surface defects such as blowholes and voids must be fully exposed. Repairs to the substrate, filling of blowholes/voids and surface levelling must be carried out using appropriate products from the Sikafloor, Sikadur and Sikagard range of materials. High spots must be removed by e.g. mechanical grinding using a diamond blade. All dust, loose and friable material must be completely removed from all surfaces before application of the product, preferably by sweeping and/or vacuuming.

Typical Data

Thickness	157 mils (4 mm)
Width	59 inches (149.46 cm)
Length	82 ft. (25 m)
Area	403 sq.ft. (37.49 m ²)
Net weight	5.9 lbs. / 10.76 sq.ft. (2.7 kg/m ²)
Gross weight	309 lbs. (140 kg)
Coverage	403 sq.ft./roll (37.49 m ²)

Storage Conditions: Store the rolls horizontally in a dry environment at temperatures between +41° F(5°C) and +86° F(30°C.)

Packaging Information:

1 Roll
Roll diameter ≈ 20 inches (50 cm)
Roll width = 59 inches (149.86 cm)

Application	Roll out the shockpad into the wet Sikafloor Comfort Adhesive and press down with Carpet and Linoleum Roller 122 lb. (e.g.55 kg) during the tack-phase. For more detailed information please refer to the current Product Data Sheet of Sikafloor Comfort Adhesive.
Cure Mechanism	Before applying Sikafloor Comfort Porefiller allow: Substrate temperature Minimum / Maximum 50°F (+10°C) 6 hrs min. / 12 hrs max. 68°F (+20°C) 3 hrs min. / 6 hrs max. 86°F (+30°C) 90 min. / 3 hrs max. Times are approximate and will be affected by changing ambient conditions, particularly temperature and relative humidity.
Limitations	Do not apply Sikafloor Comfort Regupol 6015 on substrates with rising moisture. Do not apply on substrates with a slope > 1%. Substrate Temperature 50°F (+10°C) min. / 68°F (+30°C) max. Ambient Temperature 50°F (+10°C) min. / 68°F (+30°C) max. Substrate Moisture Content Conduct quantitative anhydrous calcium chloride testing in accordance with ASTM F-1869. Maximum acceptable test result is 3 pounds per 1,000 ft ² per 24 hours. Determine the surface moisture content by using an impedance moisture meter designed for use on concrete as detailed in ASTM E-1907. Acceptable test results shall be 4% by mass or less. If over 4%, the use of Sikafloor Epocem 81/82 or Sikafloor Vapor Block will be required. Refer to specific data sheets for application instructions. Relative Air Humidity 80% r.h. max. Dew Point Beware of condensation The substrate and uncured floor must be at least 5°F (3°C) above dew point to reduce the risk of condensation or blooming on the floor finish.
Caution	May cause skin/eye/respiratory irritation. May be harmful if swallowed.
First Aid	Eyes – Hold eyelids apart and flush thoroughly with water for 15 minutes. Skin – Remove contaminated clothing. Wash skin thoroughly for 15 minutes with soap and water. Inhalation – Remove to fresh air. Ingestion – Do not induce vomiting. Dilute with water. Contact physician. In all cases contact a physician immediately if symptoms persist.
Handling & Storage	Avoid direct contact. Wear personal protective equipment (chemical resistant goggles/gloves/clothing) to prevent direct contact with skin and eyes. Use only in well ventilated areas. Open doors and windows during use. Use a properly fitted NIOSH respirator if ventilation is poor. Wash thoroughly with soap and water after use. Remove contaminated clothing and launder before reuse.
Clean Up	Use personal protective equipment (chemical resistant gloves/goggles/clothing). Without direct contact, sweep up spilled or excess product and place in suitable sealed container. Dispose of excess product and container in accordance with applicable local, state, and federal regulations.
Additional Info	Technical Data Sheets are updated periodically. To ensure the most current version is being used, visit Technical Resources on www.sikafloorusa.com . Proper material application is the responsibility of the user. Site visits made by Sika personnel are for making technical recommendations only and not for supervising or providing quality control. Before applying for protection against specific chemical environments, consult Chemical Resistance Guide or Sika Technical Service.

KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not limited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at www.sikausa.com or by calling 800-933-7452.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available online at www.sikafloorusa.com or by calling Sika's Technical Service Department at 800-933-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKASHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKASHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Visit our website at www.sikafloorusa.com

1-800-933-SIKA NATIONWIDE

Regional Information and Sales Centers. For the location of your nearest Sika sales office, contact your regional center.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 800-933-7452
Fax: 201-933-6225

Sika Canada Inc.
601 Delmar Avenue
Pointe Claire
Quebec H9R 4A9
Phone: 514-697-2610
Fax: 514-694-2792

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537

