

# PRODUCT DATA SHEET

## Sika® Fleece-120 (US)

### POLYESTER FLEECE REINFORCEMENT FOR SIKALASTIC® ROOFPRO SYSTEMS

#### PRODUCT DESCRIPTION

Non-woven, needle-punched polyester fleece reinforcement to enhance the strength and durability of Sikalastic® RoofPro roofing and waterproofing membranes.

#### USES

- Ideal for roofing and waterproofing applications displaying complex details and geometry or when accessibility is limited.
- Suitable for applications where visibility of reinforcement overlaps is an aesthetic concern.
- Ideal for applications where a one-day system installation is required.

#### CHARACTERISTICS / ADVANTAGES

- Permits wet on wet application of Sikalastic® 621 TC (US), Sikalastic®-624 WP, Sikalastic®-641 Lo VOC and Sikalastic®-644 Lo VOC
- Creates strong reinforced roofing and waterproofing membranes with enhanced tensile strength
- Fleece thickness dictates membrane thickness
- Reduces pinholing due to outgassing
- Increases puncture and tear resistance

#### PRODUCT INFORMATION

<b>Packaging</b>	48" (1.2 m) w x 150' (45.72 m)   individually bagged rolls
<b>Shelf Life</b>	Indefinite
<b>Storage Conditions</b>	Store flat and wrinkle-free in original, unopened and undamaged sealed packaging in dry conditions. Recommended to condition material to 50–77 °F (10–25 °C) before using to match liquid resin.
<b>Thickness</b>	50 mils +/- 10 (ASTM D-5729)
<b>Area Density</b>	120 g/m <sup>2</sup>

#### TECHNICAL INFORMATION

<b>Tensile Strength</b>	MD 45 lb. (20.4 kg) min. CMD 55 lb. (25 kg) min.	(ASTM D-5034)
-------------------------	---	---------------

# APPLICATION INSTRUCTIONS

## SURFACE PREPARATION

Substrate surfaces, including flashing substrates, shall be primed, clean and dry, in accordance with separate System Data Sheet.

## APPLICATION

Precut Sika® Fleece-120 (US) and dry-fit to horizontal field and vertical flashing conditions. Temporarily remove fleece. Apply approximately 2/3 of the specified resin quantity to primed substrate surface with a 1/2" (12.7 mm) nap phenolic resin core roller. Immediately fit and place Sika® Fleece-120 (US) into wet resin, overlapping reinforcement 3" (76.2 mm) along the sides and 6" (152.4 mm) at the roll ends. Apply wet roller to topside with light pressure to saturate from bottom and to ensure that air pockets are completely removed. Immediately apply the remaining 1/3 of the specified resin quantity and apply wet roller to topside with light pressure to fully saturate the membrane and achieve an even texture and appearance.

## LIMITATIONS

- Avoid creating wrinkles and creases during storage, as they will tend to be visible in finished membrane after application.
- Store rolls on end, and not on their side.
- Any repairs required to achieve a level surface must be performed prior to application (consult a Sika representative for guidance on various Sika product solutions). Surface irregularities may reflect through the cured system.
- Do not apply to a porous or damp surface where moisture vapor transmission will occur during application and cure.
- Substrate must be dry prior to application. Do not apply to a frosted, wet or damp surface. Allow sufficient time for the substrate to dry after rain or inclement weather as there is the potential for bonding problems.

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety

Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

**Sika Corporation**

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
usa.sika.com

**Sika Mexicana S.A. de C.V.**

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



Product Data Sheet  
Sika® Fleece-120 (US)  
April 2018, Version 01.01  
020816110010000013

SikaFleece-120US-en-US-(04-2018)-1-1.pdf

