



BEAT THE CLOCK

SIKAFLOOR PurCem FS

Fast Setting Polyurethane Cement Mortars & Slurries

Sikafloor® PurCem FS

Fast Setting Polyurethane Cements

When Time Is Money

Complete your PurCem installations faster with new Sikafloor PurCem FS "Fast Set". Sika has developed a rapid return to service PurCem range that dramatically reduces recoat and cure times without affecting pot life and product workability. PurCem FS uses a unique Part A with standard Parts B and C to provide you with mortar, slurry and/or coating options required for any project environment. Like all of our PurCem products, PurCem FS is phthalate free.

Get your customers back in business quickly with Sikafloor PurCem FS Systems.

- 3 hour recoating window
- Low VOCs
- Can be applied on green concrete
- Excellent thermal shock, abrasion, impact and chemical resistance
- Odorless and phthalate free
- Ideal for commercial kitchens and all FDA/USDA inspected facilities



BUILDING TRUST



Sikafloor® PurCem FS

Fast Setting Polyurethane Cements

Coverage rates and mix ratios of PurCem FS products are identical to those of PurCem standard products. For full physical characteristics, product information consult the most current Product Data Sheet available at SikafloorUSA.com or by contacting Sika Flooring Technical Services. (800.933.7452).

Cure Time	Temperature	Foot Traffic	Light Traffic	Full Cure
Sikafloor-19 NA PurCem FS	+50°F (10°C)	~ 18 Hours	~ 24 Hours	~ 6 Days
	+68°F (20°C)	~ 10 Hours	~ 18 Hours	~ 4 Days
	+86°F (30°C)	~ 4 Hours	~ 12 Hours	~ 2 Days
Sikafloor-22 NA PurCem FS	+50°F (10°C)	~ 18 Hours	~ 24 Hours	~ 6 Days
	+68°F (20°C)	~ 6 Hours	~ 18 Hours	~ 4 Days
	+86°F (30°C)	~ 4 Hours	~ 12 Hours	~ 3 Days
Sikafloor- 24 NA PurCem FS	+50°F (10°C)	~ 18 Hours	~ 24 Hours	~ 7 Days
	+68°F (20°C)	~ 8 Hours	~ 12 Hours	~ 4 Days
	+86°F (30°C)	~ 5 Hours	~ 12 Hours	~ 3 Days
Sikafloor-31 NA PurCem FS	+50°F (10°C)	~ 18 Hours	~ 24 Hours	~ 8 Days
	+68°F (20°C)	~ 12 Hours	~ 24 Hours	~ 4 Days
	+86°F (30°C)	~ 12 Hours	~ 24 Hours	~ 3 Days

Waiting/Recoat Times	Temperature	Minimum	Maximum
Sikafloor-19 NA PurCem FS	+50°F (10°C)	~ 4 Hours	~ 6 Days
	+68°F (20°C)	~ 3 Hours	~ 4 Days
	+86°F (30°C)	~ 3 Hours	~ 2 Days
Sikafloor-22 NA PurCem FS	+50°F (10°C)	~ 4 Hours	~ 24 Hours
	+68°F (20°C)	~ 3 Hours	~ 18 Days
	+86°F (30°C)	~ 3 Hours	~ 12 Days
Sikafloor- 24 NA PurCem FS	+50°F (10°C)	~ 8 Hours	~ 7 Days
	+68°F (20°C)	~ 4 Hours	~ 3 Days
	+86°F (30°C)	~ 3 Hours	~ 2 Days
Sikafloor-31 NA PurCem FS	+50°F (10°C)	~ 8 Hours	~ 24 Hours
	+68°F (20°C)	~ 6 Hours	~ 18 Days
	+86°F (30°C)	~ 5 Hours	~ 12 Days

© Sika Corporation / Flooring / 12/2019

For PurCem FS pricing and samples contact your local Sikafloor Sales Representative or Sikafloor Customer Service at 800.933.7452.