



## 1. Identification

Product name	:	Sika AnchorFix®-2 Part A
Supplier	:	Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071 USA www.sikausa.com
Telephone	:	(201) 933-8800
Telefax	:	(201) 804-1076
E-mail address	:	ehs@sika-corp.com
Emergency telephone	:	CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887
Recommended use of the chemical and restrictions on use	:	For further information, refer to product data sheet.

## 2. Hazards identification

### GHS Classification

Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 1A (Inhalation)	H350i: May cause cancer by inhalation.
Specific target organ systemic toxicity - repeated exposure, Category 1, Lungs	H372: Causes damage to organs through prolonged or repeated exposure.

### GHS label elements

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H317 May cause an allergic skin reaction. H350i May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
Precautionary Statements	:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. <b>Prevention:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read



and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves.

P281 Use personal protective equipment as required.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### 3. Composition/information on ingredients

#### Hazardous ingredients

Chemical name	CAS-No.	Concentration (%)
Quartz (SiO <sub>2</sub> )	14808-60-7	$\geq 25 - < 50 \%$
Triethylene glycol dimethacrylate	109-16-0	$\geq 10 - < 20 \%$
Quartz (SiO <sub>2</sub> ) $< 5\mu\text{m}$	14808-60-7	$\geq 10 - < 20 \%$

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
If symptoms persist, call a physician.
- In case of eye contact : Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.



- |   |   |
|---|---|
| If swallowed  | : Clean mouth with water and drink afterwards plenty of water.<br>Do not induce vomiting without medical advice.<br>Do not give milk or alcoholic beverages.<br>Never give anything by mouth to an unconscious person.<br>Obtain medical attention.   |
| Most important symptoms and effects, both acute and delayed | : Allergic reactions<br>See Section 11 for more detailed information on health effects and symptoms.<br><br>sensitizing effects<br>carcinogenic effects<br><br>May cause an allergic skin reaction.<br>May cause cancer by inhalation.<br>Causes damage to organs through prolonged or repeated exposure. |
| Protection of first-aiders                                  | : Move out of dangerous area.<br>Consult a physician.<br>Show this material safety data sheet to the doctor in attendance.  |
| Notes to physician  | : Treat symptomatically.  |

**5. Fire-fighting measures**

- |  |   |
|--|---|
| Suitable extinguishing media                   | : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.   |
| Specific extinguishing methods                 | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.<br>Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. |
| Special protective equipment for fire-fighters | : In the event of fire, wear self-contained breathing apparatus.  |

**6. Accidental release measures**

- |   |   |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.<br>Deny access to unprotected persons.   |
| Environmental precautions   | : Do not flush into surface water or sanitary sewer system.<br>If the product contaminates rivers and lakes or drains inform respective authorities.<br>Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up               | : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).<br>Keep in suitable, closed containers for disposal.   |



## 7. Handling and storage

- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Prevent unauthorized access.  
Store in original container.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Store in accordance with local regulations.
- Materials to avoid : No data available

## 8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
Quartz (SiO <sub>2</sub> )	14808-60-7	OSHA Z-3	TWA	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 respirable
		OSHA Z-3	TWA	250 mppcf / %SiO <sub>2</sub> +5 respirable
		OSHA P0	TWA	0.1 mg/m <sup>3</sup> Respirable fraction
		ACGIH	TWA	0.025 mg/m <sup>3</sup> Respirable fraction
		OSHA Z-1	TWA	0.05 mg/m <sup>3</sup> Respirable dust
Quartz (SiO <sub>2</sub> ) <5µm		OSHA Z-3	TWA	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2 respirable
		OSHA Z-3	TWA	



				250 mppcf / %SiO <sub>2</sub> +5 respirable
		OSHA P0	TWA	0.1 mg/m <sup>3</sup> Respirable fraction
		ACGIH	TWA	0.025 mg/m <sup>3</sup> Respirable fraction
		OSHA Z-1	TWA	0.05 mg/m <sup>3</sup> Respirable dust

\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**\*\*Basis**

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection**  
**Remarks** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.



Hygiene measures : Avoid contact with skin, eyes and clothing.  
 Wash hands before breaks and immediately after handling the product.  
 Remove contaminated clothing and protective equipment before entering eating areas.  
 Wash thoroughly after handling.

---

### 9. Physical and chemical properties

Appearance : viscous liquid  
 Color : gray  
 Odor : aromatic  
 Odor Threshold : No data available  
 Flash point : > 212 °F (> 100 °C)  
 Ignition temperature : No data available  
 Decomposition temperature : No data available  
 Lower explosion limit (Vol%) : No data available  
 Upper explosion limit (Vol%) : No data available  
 Flammability (solid, gas) : No data available  
 Oxidizing properties : No data available  
 pH : No data available  
 Melting point/range / Freezing point : No data available  
 Boiling point/boiling range : 482 °F (250 °C)  
 Vapor pressure : 0.01 mmHg (0.01 hpa)  
 Density : ca. 1.7 g/cm<sup>3</sup>  
 Water solubility : Note: insoluble  
 Partition coefficient: n-octanol/water : No data available  
 Viscosity, dynamic : No data available  
 Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s  
 at 104 °F (40 °C)  
 Relative vapor density : No data available  
 Evaporation rate : No data available



Burning rate	:	No data available
Volatile organic compounds (VOC) content	:	43 g/l A+B Combined

---

## 10. Stability and reactivity

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

---

## 11. Toxicological information

Not classified based on available information.

### **Skin corrosion/irritation**

Not classified based on available information.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitization**

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### **Aspiration toxicity**

Not classified based on available information.

### **Carcinogenicity**

May cause cancer by inhalation.

**IARC** Group 1: Carcinogenic to humans

Quartz (SiO <sub>2</sub> )	14808-60-7
Quartz (SiO <sub>2</sub> ) <5µm	14808-60-7



Group 2B: Possibly carcinogenic to humans

<b>NTP</b>	titanium dioxide	13463-67-7
	Known to be human carcinogen	
Titanium dioxide (13463-67-7)	Quartz (SiO <sub>2</sub> )	14808-60-7
	Quartz (SiO <sub>2</sub> ) <5µm	14808-60-7

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that cause lung cancer. Epidemiology studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

## 12. Ecological information

Other information	Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-------------------	--

## 13. Disposal considerations

### Disposal methods

Waste from residues	: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Contaminated packaging	: Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

Not dangerous goods

### IATA

Not dangerous goods

### IMDG

Not dangerous goods





**Special precautions for user**

No data available

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

---

**15. Regulatory information**

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**EPCRA - Emergency Planning and Community Right-to-Know**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA304 Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Chronic Health Hazard  
Acute Health Hazard

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

**Ozone-Depletion Potential** This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

**California Prop 65**  **WARNING:** Cancer – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

---

**16. Other information**

**HMIS Classification**

<b>Health</b>	*	3
<b>Flammability</b>		1
<b>Physical Hazard</b>		0
<b>Personal Protection</b>		X

**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

**Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 06/01/2017

Material number: 463703