



Flooring Name: Sikafloor® 200 ESD, Sikafloor 200C ESD

Description: Sikafloor®- 200 ESD and Sikafloor®- 200 ESD are pigmented, electrostatically dissipative, self-smoothing coatings.

Properties: Smooth, glossy, electrostatically dissipative.

Initial Treatment			Maintenance Cleaning		
Method	Tool	Product	Method	Tool	Product
None	None	None	Dust Mopping	TASKI Ultra Mop Frame, TASKI Large Handle, TASKI Micro Blue Pad	None
			Wet Mopping	Mop System	Stride Citrus
			Scrubber Drying Direct Method	Red or Contact Pad	Stride Citrus

Interim Cleaning			Deep Cleaning		
Method	Tool	Product	Method	Tool	Product
Maintenance Cleaning	Red Pad	Snapback TM/MC Spray Buff	Wet Scrubbing and Wet Vacuum Indirect Method	Scrubber Dryer or Single Disc Machine with Blue Pad and Wet Vacuum	Prominence
Scrubber Drying Indirect Method	Red or Contact Pad	Speedtrack			

©2023 Sika Corporation All Rights Reserved

Product Dosing: Refer to Diversey Data Sheet

When cleaning ESD control floor coatings, always follow cleaning procedure with clear water rinse to remove cleaner residue, which can inhibit electrical performance. Wash water containing high levels of dissolved minerals (hard water) may leave a residue that may reduce the effectiveness of ESD grounding of personnel.

