



Flooring Name: Sikafloor® 340 ESD

Description: Sikafloor®- 340 ESD is a UV stable and chemical resistant electrostatic control aliphatic urethane top coat.

Properties: The system is applied in two coats to provide a tough, durable ESD surface with a matte finish.

Initial Treatment			Maintenance Cleaning		
Method	Tool	Product	Method	Tool	Product
Cleaner	Mop System	None	Dust Mopping	TASKI Ultra Mop Frame, TASKI Large Handle, TASKI Micro Blue Pad	None
			Wet Mopping	Mop System	Stride Citrus
			Scrubber Drying Direct Method	Red or Contact Pad	Stride Citrus
Interim Cleaning			Deep Cleaning		
Method	Tool	Product	Method	Tool	Product
Wet Mopping Indirect Method	Mop System	Stride Citrus	Wet Scrubbing and Wet Vacuum Indirect Method	Scrubber Dryer or Single Disc Machine with Blue Pad and Wet Vacuum	Prominence
Scrubber Drying Direct Method	Red or Contact Pad	Stride Citrus			

©2023 Sika Corporation All Rights Reserved

Product Dosing: Refer to Diversey Data Sheet

When cleaning ESD control floor coatings, always follow cleaning procedure with clear water rinse to remove cleaner residue, which can inhibit electrical performance. Wash water containing high levels of dissolved minerals (hard water) may leave a residue that may reduce the effectiveness of ESD grounding of personnel.

