

PRODUCT DATA SHEET

Open Post Flashing

OPEN POST FLASHING IS A PREFABRICATED BOOT OPEN ALONG ONE SIDE

PRODUCT DESCRIPTION

Open Post Flashing is a 60 mil (1.5 mm) thick prefabricated boot open along one side to provide a simplified flashing solution for rooftop conduits and pipe penetrations when access is obstructed.

USES

For flashing rooftop conduits and pipe penetrations up to 1.25" (32 mm) in diameter in Sarnafil® and Sikaplan® roofing and waterproofing details

Areas of Application

- Rooftop conduits/pipes
- Round diameter obstructed penetrations

CHARACTERISTICS / ADVANTAGES

- Time-saving and effective method to flash rooftop conduits and pipe penetrations
- Factory fabricated
- Only one open seam to heat weld in the field

PRODUCT INFORMATION

Chemical Base	Made from Sarnafil® G 410 60 mil (1.5 mm) roofing membrane
Packaging	The Open Port Flashings can be individually ordered.
Appearance / Color	White, Tan, or Reflective Gray
Shelf Life	N/A
Storage Conditions	N/A
Dimensions	<u>Part 114610: 0.5" (12.7 mm) – 0.75" (19 mm) diameter</u> Dimensions: 8" (203 mm) high, 6" (152 mm) flange, 13" (330 mm) diameter base <u>Part 185683: 0.75" (19 mm) – 1.25" (32 mm) diameter</u> Dimensions: 8" (203 mm) high, 6" (152 mm) flange, 13.25" (337 mm) diameter base

APPLICATION INSTRUCTIONS

APPLICATION

1. Install insulation and deck sheet tight to the penetration. Secure deck sheet around the penetration according to Sika details. Securement shall be tight to the penetration so that the base plate of the Open Post Flashing will adequately cover the fasteners.
2. Wrap the Open Post Flashing around the pipe with the vertical portion tight against the penetration.
3. Mark the penetration at the top edge of the flashing and remove the prefabricated piece.
4. Place sealant around the entire penetration at the mark.
5. Wrap the Open Post Flashing around the pipe with the vertical portion tight against the penetration.
6. Tack weld the back edge of the Open Post Flashing at the slit, being sure that tight contact is maintained between the flashing and the pipe.
7. Heat weld the entire width of the vertical overlap.
8. Pre-weld and finish weld the entire base plate to the deck sheet.
9. Check all welds with a rounded screwdriver.
10. Install a stainless steel hose clamp flush with the top of the flashing.

MAINTENANCE

Standard maintenance of Sarnafil® or Sikaplan® systems should include inspections of flashings, drains, and termination sealants at least twice a year and after each storm.

AVAILABILITY/WARRANTY

Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

Warranty

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Sarnafil
100 Dan Road
Canton, MA 02021
Phone: +1 800-451-2504
Fax: +1 781-828-5365
usa.sarnafil.sika.com
webmaster.sarnafil@us.sika.com

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet
Open Post Flashing
September 2019, Version 02.01
020945012100001009

OpenPostFlashing-en-US-(09-2019)-2-1.pdf

