



## PRODUCT DATA SHEET

# SCOFIELD® Integral Color Utility

An economical blend of synthetic iron oxide pigments for coloring below-grade utility encasements and excavatable concrete

### PRODUCT DESCRIPTION

SCOFIELD® Integral Color Utility is a value blend of synthetic iron oxide pigments used to inexpensively add integral color to below grade utility encasements, excavatable concrete, Controlled Low Strength Materials (CLSM), and low strength geotechnical concrete.

### USES

It is ideal for coloring concrete designed to mark, identify, protect, and encase, utility conduit, pipes, wire cables, or fiber optic lines.

### CHARACTERISTICS / ADVANTAGES

SCOFIELD® Integral Color Utility uses pigments that are weather resistant, lightfast, and alkali resistant. It contains a minimum of 50 % post-industrial recycled material. It contains no corrosive materials and will not initiate, accelerate, or promote corrosion of reinforcing steel, metal, plastic, or rubber encasements.

### PRODUCT INFORMATION

<b>Chemical Base</b>	Synthetic iron oxide pigments.
<b>Packaging</b>	SCOFIELD® Integral Color Utility is available in 10 and 20 pound pulpable bags that can be added directly to the concrete mix.
<b>Appearance / Color</b>	Utility Red, Utility Orange, Utility Yellow, Utility Black
<b>Shelf Life</b>	24 months from date of manufacture.
<b>Storage Conditions</b>	Keep dry and moisture free.
<b>Specific Advice</b>	<u>Jobsite Samples</u> Always evaluate mix designs for color and other performance properties by creating actual sample mixtures of at least 1 cubic foot in size. Test samples for compliance with job specifications. Ensure samples do not prematurely fail, or exceed compressive strength, shrinkage, or color parameters. Do not place mix designs into service that do not meet all job specifications.

### APPLICATION INFORMATION

---

**Recommended Dosage**

Typical dosage is 1–4 pounds of SCOFIELD® Integral Color Utility material per 94 pound sack of cement. Classic concrete mix designs that use 5 sacks of concrete per cubic yard generally require 1 pound of material per sack of cement. Mix designs with very low levels of cement, heavily air entrained mixes, or low cement cellular mixes, may require higher doses to meet color specifications. Always evaluate mix designs as specified above.

---

**AVAILABILITY/WARRANTY**

at 1-800-424-9300, International 703-527-3887.  
VOC = 0 g/l

**Availability**

Scofield offers a complete line of engineered systems for coloring, texturing, and improving performance in architectural and utility concrete. Scofield Systems address specialized requirements for interior, exterior and vertical uses with compatible systems of complementary products including coloring admixtures, color hardeners, colored cementitious toppings, stains, curing compounds, sealers, coatings, repair products and texturing tools. Visit the Scofield website at [www.scofield.com](http://www.scofield.com) for further information.

**LIMITATIONS**

SCOFIELD® Integral Color Utility is not suitable for architectural flatwork, walls, or structural members. As recycled material is used to produce Utility Grade colors, they are not tightly controlled for hue, and visual color may vary.

**BASIS OF PRODUCT DATA**

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

**OTHER RESTRICTIONS**

See Legal Disclaimer.

**ENVIRONMENTAL, HEALTH AND SAFETY**

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

### Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



### Product Data Sheet

SCOFIELD® Integral Color Utility  
October 2018, Version 01.01  
021405071000000060

SCOFIELDIntegralColorUtility-en-US-(10-2018)-1-1.pdf

