



# PRODUCT DATA SHEET

## Swellstop Primer

### ADHESIVE PRIMER

#### PRODUCT DESCRIPTION

Swellstop Primer is used for adhering Sika® Greenstreak's Swellstop strip-applied waterstop to concrete.

#### USES

Swellstop Primer is used in conjunction with Sika® Greenstreak's Swellstop strip-applied waterstop in nonmoving joint applications, such as retaining walls, box culverts, penetrations, concrete pipes, vaults, slabs, elevator shafts, etc.

#### CHARACTERISTICS / ADVANTAGES

Used for adhering Sika® Greenstreak's Swellstop strip-applied waterstop to concrete.

#### PRODUCT INFORMATION

<b>Packaging</b>	Available in 1 gallon and 1 quart pails.
<b>Appearance / Color</b>	Dark brown to black
<b>Shelf Life</b>	12 months minimum when stored in the unopened, original packaging in warehouse conditions.
<b>Storage Conditions</b>	After the container has been initially opened, maintain a tight seal at room temperature not to exceed 90°F.
<b>Density</b>	% Solids 36+/-2% by weight (ASTM C771)

#### APPLICATION INFORMATION

<b>Coverage</b>	One gallon of Swellstop Primer yields 800-900 feet of Swellstop installation.
<b>Curing Rate</b>	Allow the primer to dry for a minimum of 2 hours until it is tack-free.

## APPLICATION INSTRUCTIONS

### APPLICATION METHOD / TOOLS

Brush apply a 2" wide coat of Swellstop Primer along the joint. Allow to dry for a minimum of 2 hours. Swellstop Primer Adhesive and Swellstop Waterstop should be applied on the same day.

### BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

### OTHER RESTRICTIONS

See Legal Disclaimer.

### ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

### LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety

Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

#### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)

#### Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5  
Fracc. Industrial Balvanera  
Corregidora, Queretaro  
C.P. 76920  
Phone: 52 442 2385800  
Fax: 52 442 2250537



#### Product Data Sheet

Swellstop Primer  
November 2019, Version 01.01  
020703301000000003

SwellstopPrimer-en-US-(11-2019)-1-1.pdf

