Sikagard[®] Descoglas RM Fiberglass Mat Reinforced Wall System

Epoxy Wall Coating System with Fiberglass Mat (34 mils to 39 mils)

Description	The industry standard for fiberglass mat reinforced systems, Sikagard Descoglas Fiberglass Mat Reinforced System offers the maximum thermal shock resistance for an epoxy coating system when specified with 5.94 oz woven roving mat. Thirty-plus years of performance history in the most demanding environments. Suitable for FDA inspected facilities and LEED compliant	
Where to Use	 Pharmaceutical, biotech and cosmetic manufacturing facilities Food and beverage processing facilities Health care facilities Operating rooms, scrub rooms, intensive care and therapy rooms Clean rooms and sterile environments for pharmaceutical, animal research and electronic facilities Clean in place (CIP), Vessel wash and cage wash areas Commercial kitchens, dishwasher and waste disposal areas Environments where high impact walls are required 	
Advantages	 High gloss seamless surface Resists frequent heavy duty sanitization Maximum impact and chemical resistance Excellent thermal resistance No static cling May be applied to a variety of substrates Excellent abrasion resistance Suitable for elevated temperature wash downs or exposure to steam 	





System Build Up

Coating	Product Name	Typical Thickness (mils)
Primer	Sika Bonding Primer* *Consult Sika Technical Service for recommenda- tions for drywall, Concrete Masonary Unit (CMU), Poured-in-place Concrete and other substrates.	6 - 7
1st Coat	Sikagard 215	8 - 9
Fiberglass Mat	Hexcel 1528 fiberglass fabric with F81 coating per AMS3824 utilizing wallpaper hanging techniques.	5.94 oz
Saturate Coat	Sikagard 215	8 - 9
Sealer Coat	Sikagard 215	8 - 9
Top Coats	Sikagard 307W Sterisept	4 - 5
Alternate Top Coat	Sikafloor 316N + Sikafloor SCO color Add	4 - 5



KEEP CONTAINER TIGHTLY CLOSED • KEEP OUT OF REACH OF CHILDREN • NOT FOR INTERNAL CONSUMPTION • FOR INDUSTRIAL USE ONLY

All information provided by Sika Corporation ("Sika") concerning Sika products, including but not imited to, any recommendations and advice relating to the application and use of Sika products, is given in good faith based on Sika's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with Sika's instructions. In practice, the differences in materials, substrates, storage and handled tions, actual site conditions and other factors outside of Sika's control are such that Sika assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the Sika product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). Sika reserves the right to change the properties of its products without notice. All sales of Sika product(s) are subject to its current terms and conditions of sale which are available at www.sikacorp.com or by calling 800-933-7452.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Material Safety Data Sheet which are available online at <u>www.sikafloorusa.com</u> or by calling Sika's Technical Service Department at 800-833-7452. Nothing contained in any Sika materials relieves the user of the obligation to read and follow the warnings and instruction for each Sika product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use.

Sika warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical proper-ties on the current Technical Data Sheet if used as directed within shelf life. User determines suitability of product for intended use and as-sumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NOOTHERWARRANTIESEXPRESSORIMPLIEDSHALLAPPLYINCLUDINGANYWARRANTYOFMERCHANTABILITYORFITNESSFORAPARTICULAR PURPOSE.SIKASHALLNOTBELIABLEUNDERANYLEGALTHEORYFORSPECIALORCONSEQUENTIALDAMAGES.SIKASHALLNOTBERESPONSIBLE FOR THE USE OF THIS PRODUCTINAMANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sika Mexicana S.A. de C.V. Carretera Libre Celaya Km. 8.5

Fracc. Industrial Balvanera

Corregidora, Queretaro

Phone: 52 442 2385800 Fax: 52 442 2250537

C.P. 76920

Visit our website at www.sikafloorusa.com

Regional Information and Sales Centers. For the location of your nearest Sika sales office, contact your regional center Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071 Phone: 800-933-7452 Fax: 201-933-6225

Sika Canada Inc. 601 Delmar Avenue Pointe Claire Quebec H9R 4A9 Phone: 514-697-2610 Fax: 514-694-2792

1-800-933-SIKA NATIONWIDE

