



1. APPLY ONE COAT OF SIKAFLOOR FTP PRIMER AT 5 MILS (300 SQ. FT./GAL).
2. WATERPROOFING OPTIONS
 - A. APPLY ONE COAT OF SIKALASTIC 710 BASE COAT AT 32 MILS (50 SQ.FT./GAL) OR
 - B. APPLY ONE COAT OF SIKALASTIC 720 BASE COAT AT 23 MILS (73 SQ.FT./GAL)
3. TOP COAT OPTIONS
 - A. APPLY ONE COAT OF SIKALASTIC 715 POLYURETHANE TOP COAT AT 14-16 MILS, (100-115 SQ.FT./GAL, SECOND COAT OPTIONAL) OR,
 - B. APPLY ONE COAT OF SIKALASTIC 745 POLYURETHANE TOP COAT AT 12-18 MILS, (90-133SQ.FT./GAL, SECOND COAT OPTIONAL) OR,
 - C. APPLY ONE COAT OF SIKALASTIC 710 POLYURETHANE TOP COAT AT 16 MILS, (100 SQ.FT./GAL, SECOND COAT OPTIONAL) OR,
 - D. APPLY ONE COAT OF SIKALASTIC 720 POLYURETHANE TOP COAT AT 12 MILS, (133SQ.FT./GAL, SECOND COAT OPTIONAL)
4. BROADCAST OPTIONS
 - A. FOR A TOPCOAT FOLLOWED BY THE OPTIONAL SECOND TOPCOAT, BROADCAST 20/40 GRIT SAND INTO THE WET TOPCOAT UNTIL REFUSAL. AFTER CURE, REMOVE EXCESS AGGREGATE BEFORE PROCEEDING WITH THE OPTIONAL SECOND TOP COAT.
 - B. FOR A TOPCOAT FOLLOWED BY THE THIN SET, BROADCAST 16/20 MESH, CRACK ANGULAR SAND INTO THE WET TOPCOAT UNTIL REFUSAL. AFTER CURE, REMOVE EXCESS AGGREGATE BEFORE PROCEEDING WITH THE THIN SET.
5. APPLY THIN SET MORTAR



1-800-933-SIKA (7452)
www.sikausa.com

JOB NAME:

DETAIL TITLE

THIN SET TILE DETAIL

SCALE:

N.T.S.

DATE:

9/13

FILE NO.:

DRW. NO.:

TR-11

AS A MANUFACTURER OF CONSTRUCTION PRODUCTS, SIKA CORPORATION PROVIDES GENERIC DETAILS AS A GENERAL GUIDE FOR INFORMATION PURPOSES ONLY. THESE DETAILS ARE NOT INTENDED TO REPLACE SOUND ENGINEERING AND ARCHITECTURAL PRACTICES AND SHOULD NOT BE RELIED UPON FOR THAT PURPOSE. SIKA CORPORATION ASSUMES NO LIABILITY WITH RESPECT TO THE DESIGN OF THE SYSTEM. THE ARCHITECT, CONSULTANT AND/OR ENGINEER OR DESIGN PROFESSIONAL FOR A PARTICULAR PROJECT BEARS THE SOLE RESPONSIBILITY FOR THE DESIGN OF THE SYSTEM, FOR THE PREPARATION AND APPROVAL OF THE PROJECT SPECIFICATIONS, DETAILS AND SHOP DRAWINGS, AND FOR DETERMINING THEIR SUITABILITY FOR A PARTICULAR PROJECT OR APPLICATION. WHILE SIKA PROVIDES GENERAL INSTRUCTIONS FOR THE INSTALLATION OF ITS MATERIALS, THE MEANS AND METHODS USED BY THE CONTRACTOR FOR MATERIAL STORAGE, SUBSTRATE EVALUATION, SURFACE PREPARATION, AND THE INSTALLATION OF BOTH SIKA AND NON-SIKA MATERIALS ARE THE RESPONSIBILITY OF THE CONTRACTOR. THE CONTRACTOR MUST ALWAYS READ AND FOLLOW THE WARNINGS AND INSTRUCTIONS ON SIKA PRODUCT LABELS, TECHNICAL DATA SHEETS, AND MATERIAL SAFETY DATA SHEETS AVAILABLE AT WWW.SIKAUSA.COM. SIKA CORPORATION MAKES NO WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, AS TO THE CONTENT OF THIS GUIDE DETAIL. SIKA SHALL NOT BE RESPONSIBLE UNDER ANY LEGAL THEORY TO ANY THIRD PARTY FOR ANY DIRECT OR CONSEQUENTIAL DAMAGES OF ANY KIND ARISING FROM THE USE OF THIS GUIDE DETAIL. ALL PRODUCTS AND SERVICES PROVIDED BY SIKA CORPORATION ARE SUBJECT TO ITS TERMS AND CONDITIONS OF SALE AVAILABLE AT WWW.SIKAUSA.COM.