

PRODUCT DATA SHEET

Drainage Panel 900

DRAINAGE PANEL 900 IS A PREFABRICATED COMPOSITE PANEL

PRODUCT DESCRIPTION

Drainage Panel 900 is a high quality prefabricated composite panel with a 0.40" (10.2 mm) profile designed to provide continuous free flow of water in horizontal applications. It is recommended for medium traffic areas where high flow rates are required. The drainage panel has a three dimensional high impact polymeric core and woven monofilament fabric. Water passes freely into the drain core, where it is gravity fed to the drain or to discharge. If the overburden is landscaping or soil, use Drainage Panel 980. For heavy traffic areas, use Drainage Panel 990.

USES

To provide continuous free flow of water in horizontal applications

Areas of Application

- Plaza Decks

CHARACTERISTICS / ADVANTAGES

- Enhances the performance of a Sika plaza deck system
- Relieves hydrostatic pressure build up
- Provides a uniform flow path for water to escape
- High flow capacity

PRODUCT INFORMATION

Chemical Base	High impact resistant polypropylene core and woven monofilament fabric
Packaging	4 ft x 50 ft (1.2 m x 15.2 m) roll, 50 lbs per roll
Shelf Life	N/A
Storage Conditions	N/A
Thickness	0.40" (10.2 mm) (ASTM D-1777)
Unit weight	0.39 lb/ft ² (1.91 kg/m ²)

TECHNICAL INFORMATION

Resistance to Static Puncture	100 lb (0.44 kN) (ASTM D-4833)
Tensile Strength	Grab Tensile 365 lb (1.62 kN) (ASTM D-4632)
Opening Size	40 EOS, US Sieve (0.42 mm) (ASTM D-4751)
Flow Rate	Core Flow 21 gpm/ft width (261 lpm/m width)* (ASTM D-4716) <small>* Q at 3,600 psf & Hydraulic Gradient = 1.0 (300 hrs). Information contained herein is offered solely for the customer's consideration, investigation and verification. Determination of suitability for use is the sole responsibility of the user.</small>
	Fabric Flow 145 gpm/ft width (5,907 lpm/m width) (ASTM D-4491)

APPLICATION INSTRUCTIONS

APPLICATION

Drainage Panel 900 is installed by an authorized Sika Sarnafil® Waterproofing Applicator. The drainage panel is loosely laid over the completed waterproofing system. Panels are interlocked or snapped together to form one continuous layer of material. Consult with Sika Sarnafil® Waterproofing System Specifications for further information.

MAINTENANCE

Standard maintenance of roofs should include inspection of flashings, drains and termination sealants at least twice a year and after each storm.

AVAILABILITY/WARRANTY

Availability

From Sika Corporation – Roofing Authorized Applicators for use within Sarnafil or Sikaplan systems.

Warranty

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
Drainage Panel 900
February 2020, Version 04.02
020945051350001004

DrainagePanel900-en-US-(02-2020)-4-2.pdf

