



PRODUCT DATA SHEET

Sikacryl® Ready-Mix Concrete Patch

Acrylic-based, textured concrete patch for spalls/large cracks

PRODUCT DESCRIPTION

Sikacryl® Ready-Mix Concrete Patch is an easy to use, acrylic-based, textured concrete patch for repairing spalls and cracks in concrete and masonry that cures to a tough and durable finish.

USES

Sikacryl® Ready-Mix Concrete Patch can be used on concrete and masonry surfaces, such as:

- Sidewalks
- Steps
- Balconies
- Foundations
- Patios, and more.

CHARACTERISTICS / ADVANTAGES

- For vertical and horizontal surfaces
- Textured to blend with concrete
- Easy water clean up
- Good adhesion
- Simple application
- Won't shrink or crack

PRODUCT INFORMATION

Packaging	1 qt. (.94 L) plastic container, 12/case 1 gal. (3.8 L) plastic container, 2/case
Appearance / Color	Gray
Shelf Life	24 months in original, unopened containers
Storage Conditions	Store away from extreme heat or cold. Store in original container between 40 to 90 °F (4 to 32 °C)

APPLICATION INFORMATION

Coverage	Container Size	Coverage	Application Thickness
	1 quart	20ft ²	1/32 in. (0.8mm)
	1 gallon	80ft ²	1/32 in. (0.8mm)

Layer Thickness	Minimum	<u>1/32"</u>
	Maximum	<u>1/4"</u>
For applications deeper than 1/4", apply in multiple layers. Final application thickness should not exceed 1/2".		
Ambient Air Temperature	40 to 90 °F (4 to 32 °C)	
Cure Time	Full Cure: Minimum of 1 day at 1/4 in. (6.3 mm) depth depending on temperature	
Set Time	2 to 4 hours	

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

LIMITATIONS

- Substrate must be dry prior to application (minimum 48 h)
- Check color before using, will not change once cured
- Protect from freezing
- Do not apply at temperatures below 40 °F (4 °C)
- Allow the material to dry between applications
- Cracks or spalls deeper than 1/4 in. (6.3 mm), will require two or more applications
- Allow to dry before subjected to water
- Not recommended for areas exposed to vehicular traffic
- **Do not apply if rain or freezing temperatures are forecasted before full cure can occur.**
- **Do not apply over 1/4 in. in one application**
- **Final application thickness should not exceed 1/2 in.**

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

Surface should be clean, sound, dry, and free from dirt and loose particles. For best results, use a wire brush to clean off any loose particles or excess dirt or dust. Area to be repaired should accept moisture penetration.

MIXING

Stir material thoroughly until a uniform appearance and

consistency is achieved prior to use.

APPLICATION

Use a putty knife or trowel to apply product to surface. Ensure that enough product is pushed into crack or hole to provide coverage. Tool as required. Areas greater than 1/4 in. (6.3 mm) deep will require two or more applications. For applications greater than 1/4 in. (6.3 mm) depth, allow the material to dry between applications. Apply at a minimum thickness of 1/32 in. (0.8 mm). Allow repaired area to dry and fully cure for at least 24 hours, depending on temperature, humidity and depth of repair.

CLEANING OF TOOLS

Clean tools immediately after use with water.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- **KEEP CONTAINER TIGHTLY CLOSED**
- **KEEP OUT OF REACH OF CHILDREN**
- **NOT FOR INTERNAL CONSUMPTION**

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole

remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs.
NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 201-933-8300.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

Sikacryl® Ready-Mix Concrete Patch
May 2026, Version 01.04
021840303000000002

SikacrylReady-MixConcretePatch-en-US-(05-2026)-1-4.pdf

