

PRODUCT DATA SHEET

SikaProof® Tape A+

SELF-ADHESIVE TAPE FOR INTERNAL JOINTING OF SIKAPROOF A+ WATERPROOFING SYSTEM

PRODUCT DESCRIPTION

SikaProof® Tape A+ is a self-adhesive tape based on a polyacrylate adhesive with a carrier film and a release liner.

USES

SikaProof® Tape A+ may only be used by experienced professionals.

- Sealing and bonding overlap joints, connections and details within the SikaProof® A+ membrane system.

CHARACTERISTICS / ADVANTAGES

- Fully bonded to the concrete structure (identical to SikaProof® A+)
- No lateral water migration between the concrete structure and the membrane system
- High adhesion and sealing capability, especially in cold and damp conditions
- Simple and fast to install

PRODUCT INFORMATION

Packaging	2 rolls packed in one cardboard box	
	Individual roll size	Length: 25 m (82 ft) Width: 150 mm (6 in)
Appearance / Color	Top layer	Light grey hybrid bonding layer with yellow waterproofing layer
	Bottom layer	Transparent polyacrylate adhesive covered with a white release liner
Shelf Life	18 months from date of production	
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +40 °F and +86 °F. Always refer to packaging.	
Thickness	1.80 mm (0.07 in)	

SYSTEM INFORMATION

APPLICATION INFORMATION

Ambient Air Temperature	+40 °F min. / +110 °F max.
Substrate Temperature	+40 °F min.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface is the grey SikaProof® A+ hybrid bonding layer. It must be dry (or slightly damp), clean and free of any materials that could impair the adhesion. If the substrate requirements are not achieved, suitable measures must be taken. Contact Sika® Technical Services for more information.

APPLICATION METHOD / TOOLS

Strictly follow installation procedures as defined in method statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

Installation Procedure

Remove the release liner, apply onto the grey SikaProof® A+ membrane side and press tape firmly using a pressure roller.

AVAILABILITY/WARRANTY

- Sika® Method Statement: SikaProof® A+
- Sika® Application Manual: SikaProof® A+
- Product Data Sheet: SikaProof® A+ 12

LIMITATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Do not install SikaProof® Tape A+ during continuous or prolonged rain or snowfall.
- The substrate quality and conditions must be fulfilled or appropriate measures must be taken. Contact Sika® Technical Services for more information.
- SikaProof® Tape A+ is not permanently UV resistant.
- The structural concrete must be placed within 90 days after the SikaProof® A+ membrane system is installed.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

See Legal Disclaimer.

ENVIRONMENTAL, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulations is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1% (w/w).

LEGAL DISCLAIMER

- **KEEP CONTAINER TIGHTLY CLOSED**
- **KEEP OUT OF REACH OF CHILDREN**
- **NOT FOR INTERNAL CONSUMPTION**
- **FOR INDUSTRIAL USE ONLY**
- **FOR PROFESSIONAL USE ONLY**

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or

replacement of this product exclusive of any labor costs.
NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet
SikaProof® Tape A+
August 2019, Version 02.01
020704210220000019

SikaProofTapeA+-en-US-(08-2019)-2-1.pdf

