

PRODUCT DATA SHEET

SikaTile®-905 Fat Mud

MORTAR SETTING BED FOR VERTICAL SURFACES

PRODUCT DESCRIPTION

SikaTile®-905 Fat Mud is a Portland Cement based tile mortar, pre-blended and packaged in 50 lb. bag for easier handling.

USES

Mortar setting bed on vertical walls over an appropriate membrane and metal lath. Available in Northern California region only.

CHARACTERISTICS / ADVANTAGES

- For use as a scratch coat and wall render, or as a concrete patch from 1/4" to 2" (6 mm to 5 cm)
- Easy to use

APPROVALS / STANDARDS

Raw materials meet or exceed the following standards:

- Portland Cement Type II/V ASTM C 150
- Mortar Sand ASTM C 144
- Type S Lime ASTM C 207

PRODUCT INFORMATION

Packaging	<ul style="list-style-type: none"> ▪ 50 lb (22.7 kg) bag ▪ Bulk/Silo - call for details
Appearance / Color	Gray powder
Shelf Life	12 months from date of production if stored properly in original, unopened and undamaged sealed packaging
Storage Conditions	Store dry at 40–95 °F (4–35 °C). Protect from moisture. If damp, discard material

APPLICATION INFORMATION

Mixing Ratio	1 gal. and 1 pt. (4.25 L) per bag		
Coverage	Thickness	50 lb. bag	1 ton silo
	1/2" (1.27 cm)	8 ft ² (0.74 m ²)	400 ft ² (37.16 m ²)
(Coverage figures do not include allowance for surface profile and porosity or material waste)			

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

ENVIRONMENTAL, HEALTH AND SAFETY

Keep container tightly closed. Keep out of reach of children. Not for internal consumption. For industrial use only. For professional use only. For further information and advice regarding transportation, handling, storage and disposal of chemical products, users should refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety related data. Read the current actual Safety Data Sheet before using the product. In case of emergency, call CHEMTREC at 1-800- 424-9300, International 703-527-3887.

DIRECTIVE 2004/42/CE - LIMITATION OF EMISSIONS OF VOC

0 g/l

APPLICATION INSTRUCTIONS

MIXING

Mix approximately 1 gallon and 1 pint (4.25 L) of clean potable water in the temperature range of 50 to 80 °F per bag. Mix thoroughly until a consistent mix is obtained.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

SikaTile®-905 Fat Mud
December 2020, Version 01.02
021710101000000049

SikaTile-905FatMud-en-US-(12-2020)-1-2.pdf

