

PRODUCT DATA SHEET

Sikaplan® Walkway-20

Thermoplastic heat welded walkway

PRODUCT DESCRIPTION

Sikaplan® Walkway-20 is a thermoplastic rolled-out, heat welded walkway used to protect the Sarnafil® or Sikaplan® roof membrane and provide a path for foot traffic.

USES


To provide a walkway and protect the roof membrane from foot traffic.

AREAS OF APPLICATION

- New Roofs
- Recover Roofs
- Mechanically Fastened Systems
- Adhered Systems

CHARACTERISTICS / ADVANTAGES

- Dimensionally stable and durable
- Easy to install



PRODUCT INFORMATION

Chemical Base	Polyvinyl chloride (PVC)
Packaging	Provided in rolls on wood pallets
Shelf Life	N/A
Storage Conditions	N/A
Appearance / Color	<ul style="list-style-type: none">Top surface: Dark grayBottom surface: Dark gray
Top surface	Texturized (pyramid)
Length	32.8 ft (10 m) (+/- 5%) (EN 1848-2)
Width	39" (1 m) (+/- 1%) (EN 1848-2)
Overall Thickness	79 mil (2 mm) (-5% / +10%) (EN1849-2) Depth of embossing: ~16 mil (0.40 mm)
Mass per Unit Area	0.51 lb/ft ² (2.5 kg/m (+/- 20%)) (EN 1849-2)

TECHNICAL INFORMATION

Tensile Strength	min. 202 lbf (900 N) (EN 12311-2)					
Elongation	<table><tr><td>longitudinal</td><td>min. 15%</td><td rowspan="2">(EN 12311-2)</td></tr><tr><td>transversal</td><td>min. 15%</td></tr></table>	longitudinal	min. 15%	(EN 12311-2)	transversal	min. 15%
longitudinal	min. 15%	(EN 12311-2)				
transversal	min. 15%					

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

AVAILABILITY/WARRANTY

AVAILABILITY

From Sika Corporation – Roofing Authorized Applications for use within Sarnafil or Sikaplan systems.

WARRANTY

Upon successful completion of the installed roof by the Sika Authorized Applicator, Sika Corporation will provide a warranty to the Building Owner via the Sika Authorized Applicator.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC

at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

Roofing membrane to receive Sikaplan Walkway-20 shall be clean and dry. Chalk lines on the deck sheet to indicate the location of walkway.

Check all existing deck sheet seams that are to be covered by Sikaplan Walkway-20 with a rounded screwdriver and reweld any inconsistencies before the walkway installation.

APPLICATION

Adhered Roofs:

Apply a continuous coat of Sarnacol 2170 or Sarnacol 2170 VC membrane adhesive to the deck sheet and the back of Sikaplan Walkway-20 in accordance with the Application Instructions outlined in the membrane adhesive product data sheet. Do not apply adhesive in the areas of the deck sheet where the Sikaplan Walkway-20 will be hot-air welded. Roll Sikaplan Walkway-20 into the adhesive and press into place with a minimum 75 lb (34 kg) steel roller. Hot-air weld the entire perimeter of Sikaplan Walkway-20 to the deck

sheet. Check all welds with a rounded screwdriver. Reweld any inconsistencies.

Mechanically Attached Roofs:

Adhering Sikaplan Walkway-20 to the deck sheet with Sarnacol 2170 or Sarnacol VC membrane adhesive as noted in Adhered Roofs is optional. Install Sikaplan Walkway-20 over the deck sheet and hot-air weld the perimeter leaving intermittent weeps as needed of unwelded Sikaplan Walkway-20 along the low side for drainage. Check all welds with a rounded screwdriver. Reweld any inconsistencies.

MAINTENANCE

Standard maintenance of Sarnafil or Sikaplan systems should include regular inspections of flashings, drains, and termination sealants at least twice a year and after each storm.

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.

Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2385800
Fax: 52 442 2250537



Product Data Sheet

Sikaplan® Walkway-20
January 2022, Version 03.03
020905071000201001

SikaplanWalkway-20-en-US-(01-2022)-3-3.pdf

