

PRODUCT DATA SHEET

SikaProof® Patch-200 B

SELF-ADHESIVE TAPE FOR EXTERNAL JOINTING OF THE SIKAPROOF® A WATERPROOFING SYSTEM.

PRODUCT DESCRIPTION

SikaProof® Patch-200 B is a self-adhesive tape, consisting of a SikaProof® membrane laminated with a Butyl-adhesive that is covered with a release liner.

USES

SikaProof® Patch-200 B may only be used by experienced professionals.

SikaProof® Patch-200 B is used for post-sealing of joints, penetrations as well as damages outside on the membrane side of the SikaProof® A system.

CHARACTERISTICS / ADVANTAGES

- High watertightness
- Weathering resistant with temporary UV-stability
- High adhesion
- High durability of the Butyl-adhesive
- Easy and fast to install

PRODUCT INFORMATION

Packaging	1 roll, packed in one cardboard box
Appearance / Color	White release liner over black adhesive on a light yellow membrane.
Shelf Life	18 months shelf life from date of production if stored properly in undamaged, unopened, original sealed packaging.
Storage Conditions	Dry storage at temperatures from +40°F up to +85°F. Protect from direct sunlight, rain, snow, ice, humidity, etc. Store in a horizontal position. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.
Thickness	2.20 mm (0.087 in)

SYSTEM INFORMATION

System Structure	Accessory: SikaProof® Patch-200 B is an ancillary product for the SikaProof® A sheet membrane waterproofing system.
-------------------------	---

APPLICATION INFORMATION

Ambient Air Temperature +40 °F min. / +95 °F max.

Substrate Temperature +40 °F min. / +95 °F max.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface is the light yellow membrane side of the SikaProof® A membrane. It must be dry, clean and free of any materials that could impair the adhesion.

APPLICATION METHOD / TOOLS

SikaProof® Patch-200 B is a cold-applied and post-applied self-adhesive tape to seal joints, connections, penetrations and possible damages of the membrane on the outside membrane side of the SikaProof® A system. There is only a pressure roller required, to press the tapes firmly onto the membrane surface.

For further more detailed information about the installation method, please refer to the SikaProof® A membrane Product Data Sheet and the Method Statement.

LIMITATIONS

SikaProof® A system must only be installed by trained and approved Sika contractors.

SikaProof® Patch-200 B is not UV stabilised and can not be installed on structures permanently exposed to UV light and weathering.

Do not apply the SikaProof® Patch-200 B during continuous or prolonged rainfall.

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

OTHER RESTRICTIONS

Sika Corp. Inc.
201 Polito Avenue
Syndhurst, NY 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com

Sika Mexicana S.A. de C.V.
Carretera Libre Celaya Km. 8.5
Fracc. Industrial Balvanera
Corregidora, Queretaro
C.P. 76920
Phone: 52 442 2365800
Fax: 52 442 2250537

ENVIRONMENTAL, HEALTH AND SAFETY



Product Data Sheet
SikaProof® Patch-200 B
October 2019, Version 01.01
020704210220000007

A Material Safety Data Sheet following EC- Regulation 1907/2006, Article 31 is not required to bring this product to the market, to transport, or to use it. The product does not damage the environment when used as specified.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

SikaProofPatch-200B-en-US-(10-2019)-1-1.pdf

