

PRODUCT DATA SHEET

SikaProof® Tape A+ N

SELF-ADHESIVE TAPE FOR INTERNAL JOINTING AND DETAILING OF SIKAPROOF® A+ WATERPROOFING SYSTEM

PRODUCT DESCRIPTION

SikaProof® Tape A+ N is a self-adhesive tape based on a polyacrylate adhesive with a carrier film and a release liner.

USES

- Sealing and bonding overlap joints, connections and details within the SikaProof® A+ system.

CHARACTERISTICS / ADVANTAGES

- Fully and permanently bonded to the concrete structure
- No lateral water underflow between the concrete structure and the membrane system
- High adhesion and sealing capability in cold and damp conditions
- Simple and fast to install

PRODUCT INFORMATION

Packaging	4 rolls packed in one cardboard box	
	Roll length	82 ft 25 m
	Roll width	4.7 (±0.2) in 120 (±5) mm
Appearance / Color	Top layer	Light grey hybrid bonding layer with yellow waterproofing layer
	Bottom layer	Transparent polyacrylate adhesive covered with transparent release liner
Shelf Life	18 months from date of production	
Storage Conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +40 °F (+5 °C) and +85 °F (+30 °C). Always refer to packaging.	
Thickness	66 (+6 / -3) mils 1.68 (+0.17 / -0.08) mm	

APPLICATION INFORMATION

Ambient Air Temperature	Maximum	+110 °F +43 °C
	Minimum	+40 °F +5 °C

SYSTEM INFORMATION

System Structure

SikaProof® Tape A+ N is a system component for internal jointing of the SikaProof® A+ system. For more detailed information, refer to Sika® Method Statement: SikaProof® A+ system

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

IMPORTANT

Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

IMPORTANT

Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

SUBSTRATE QUALITY

The contact surface is the grey SikaProof® A+ bonding layer. It must be dry or slightly damp, clean and free of any materials that could impair adhesion.

Application outside of specified application conditions

Note: Under certain circumstances, the Product can be applied in conditions other than the ones specified in this data sheet. However, this requires specific precautions and application methods.

- Contact Sika technical services for more information.

APPLICATION

IMPORTANT

Exposure to UV or weathering

The Product is not resistant to permanent UV exposure or weathering.

- Protect as soon as possible but not later than 90 days after application
- Remove the release liner
 - Apply onto the grey SikaProof® A+ membrane side
 - Press on firmly using a pressure roller

OTHER RESTRICTIONS

See Legal Disclaimer.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and

Conditions of Sale which are available at
<https://usa.sika.com/en/about-us/terms-conditions-of-sale.html> or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet
SikaProof® Tape A+ N
August 2025, Version 02.02
02072030800000021

SikaProofTapeA+N-en-US-(08-2025)-2-2.pdf

