

# PRODUCT DATA SHEET

## Sikafloor® WP-8

### Sports Floor 450 Finish

#### PRODUCT DESCRIPTION

Oil modified urethane varnish, 50% solids. A clear coating formulated to provide a durable, solid protective film.

#### USES

Sikafloor® WP-8 may only be used by experienced professionals.

New and existing wood sports floors in public and private schools, universities, professional arenas, and health clubs.

#### CHARACTERISTICS / ADVANTAGES

- Superior Gloss
- Superior abrasion resistance
- Superior lightness in color
- Excellent rubber burn resistance
- Excellent film hardness
- 450 VOC compliant

#### APPROVALS / STANDARDS

##### MFMA TESTS:

Sanding	Pass
Hardness	Pass
Abrasion Resistance	Pass
Flexibility	Pass
Coefficient of Friction	Pass
Maintenance	Pass

#### PRODUCT INFORMATION

<b>Packaging</b>	Product is available in 5-gallon (18.9 L) containers.
<b>Shelf Life</b>	2 years in original unopened container under proper storage conditions.
<b>Storage Conditions</b>	Store dry between 40° - 90°F (5°- 32°C).
<b>Appearance / Color</b>	4 - 6 (ASTM D-1544)
<b>Solid content by mass</b>	7.4 - 7.6 lbs. (ASTM D-1475)
<b>Viscosity</b>	40 - 70 cps (ASTM D-1545)
<b>Volatile organic compound (VOC) content</b>	<450 g/L <b>Flash Point:</b> 105°F (40.5°C) (ASTM D-56)

## TECHNICAL INFORMATION

Gloss level	(60°) 90+	
Chemical Resistance	Stain Resistance	Pass
	Alcohol Resistance	Pass
	Naphtha Resistance	Pass
	Cola Resistance	Pass
	Beer Resistance	Pass
	Perspiration Resistance	Pass

## APPLICATION INFORMATION

Coverage	400-500 sq. ft/ gal. (37 m2-46.5m2/L)
Cure Time	Allow over night cure (16 hrs min. 36 hrs max.) before recoating. Finish with a second coat of WP-8. Allow 48 hours cure before light traffic and 5 - 7 days before athletic activities. Adequate ventilation is imperative during the curing process. Dry times will vary based upon the drying conditions. Do not apply when temperature is above 95° F (35°C) or below 65° F (18°C), or when humidity is above 80%. Clean up with mineral spirits.

## BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

ensure the most current version is being used, visit Technical Resources on [www.sikafloorusa.com](http://www.sikafloorusa.com).

## AVAILABILITY/WARRANTY

Proper material application is the responsibility of the user. Site visits made by Sika personnel are for making technical recommendations only and not for supervising or providing quality control. Before applying for protection against specific chemical environments, consult Chemical Resistance Guide or Sika Technical Service.

- 1. SPONTANEOUS COMBUSTION:** Dust created from screening oil based finishes and rags soaked with oil and dust can auto-ignite causing a fire. DO NOT store or throw away the dust and oil soaked rags into a closed vacuum or trash can. Immerse the dust in water and open the rags to air dry before discarding the waste. High temperatures, high humidity and freshly applied seal increase the potential for a fire.
2. Long term overexposure to solvents have been associated with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
3. In case of a spill absorb with inerts like sawdust or "oil dry" and wipe clean with Mineral Spirits. Dispose in accordance with local regulations.
4. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture, or weld on or near container.
5. Technical Data Sheets are updated periodically. To

## Trouble Shooting

<u>Problem Observed</u>	<u>Possible Causes</u>
Slow Dry:	Low curing temperatures, High humidity, Lack of ventilation, and air movement after application.
Streaks:	Product applied too thin.
Fisheyes:	A foreign material on the surface, like oil, grease, or silicone.
Wrinkling:	Recoating too soon, Too heavy an application, puddling the finish.
Bubbling:	Overworking the product with applicator, shaking the finish before applying, High temperatures during application.
Peeling:	Improper floor preparation.
Dirt Particles:	Applicator Not "De-Fuzzed" loose fibers in the film, Room vents not sealed during the application.
Screen Marks:	Using a too aggressive screen between coats.

## Handling & Storage

Keep away from heat, sparks, sunlight, electrical equipment or flame. **VAPORS MAY IGNITE AND EXPLODE. DO NOT SMOKE.** Open doors and windows during use. Use adequate local and mechanical ventilation. Wear protective equipment (chemically resistant gloves/goggles/clothing) to prevent direct contact with skin and eyes. Use properly fitted NIOSH vapor cartridge respirator if ventilation is poor. Wash thoroughly with soap and water after use. Remove contaminated clothing after use. Store product in tightly sealed containers in a cool, dry well ventilated area at temperatures between 40° F and 90°F away from ignition sources.

## ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

### Caution

**WARNING: COMBUSTIBLE, IRRITANT:** Contains Mineral Spirits (Mixture), Xylene (CAS: 1330-20-7), Ethylbenzene (CAS: 100-41-4). **Keep away from heat, sparks, sunlight, electrical equipment or flame. VAPORS MAY IGNITE AND EXPLODE. DO NOT SMOKE.** May cause eye/skin/respiratory irritation. May be harmful if swallowed. Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain, liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal. **WARNING:** This product contains a chemical known to the State of California to cause cancer.

### First Aid

**Eyes** – Hold eyelids apart and flush thoroughly with water for 15 minutes. **Skin** – Remove contaminated clothing. Wash skin thoroughly for 15 minutes with soap and water. **Inhalation** – Remove to fresh air. Ingestion – Do not induce vomiting. Dilute with water. **Contact physician. In all cases contact a physician immediately if symptoms persist.**

### Product Data Sheet

Sikafloor® WP-8

January 2023, Version 01.02

020812040020000062

# APPLICATION INSTRUCTIONS

## SURFACE PREPARATION

### Previously coated floors

A test patch is strongly recommended to determine adhesion compatibility over a previous water base, or unknown finish.

1. Remove any masking tape or gum with a putty knife. Clean the floor of dirt, dust mop treatments, etc with a neutral cleaner.
2. Allow the floor to dry thoroughly.
3. Screen the floors with #100 grit screens (250 sq. ft per side; 23m<sup>2</sup>) until the gloss is removed.
4. Tack rag the floor using water.
5. Proceed to Finish coats.

### Newly installed floors or sanded to bare wood

1. Screen the floor using #100 grit screens (250 sq. ft per side, 23m<sup>2</sup>).
2. Vacuum, then tack rag the floor with water.
3. Allow the floor to dry to a dull, glossless surface.

### Seal coat application

1. With a conventional lambswool or foam applicator or weighted T-bar, seal the bare wood with Sikafloor WP-4.
2. Allow 2 - 4 hours dry with good ventilation for each coat.
3. Minimum of two coats of Sikafloor WP-4 is recommended.
4. Remove raised grain with a #120 grit screen, then tack rag with water.
5. Line marking paint can then be applied.

### Line marking:

1. Before using paint every color should be tested for compatibility, not just brands.
2. Apply line markings between the second and third coats. Follow the directions on the paint label for application.
3. Lay out the court with masking tape as required and apply the paint.
4. To ensure crisp lines allow paint to dry 1-2 hours before pulling up the tape.
5. Allow the lines to dry per manufacturers directions.
6. Abrade the lines lightly with #120 grit screens.

## MIXING

THIS PRODUCT IS DESIGNED TO BE USED AS IS DO NOT THIN OR REDUCE WITH SOLVENTS.

## APPLICATION

With a conventional lambswool or foam applicator or weighted T - bar, apply Sikafloor WP-8. Do not puddle finish.

## MAINTENANCE

### CLEANING

In case of spill, eliminate all ignition and heat sources.  
**Keep away from heat, sparks, sunlight, electrical**

**equipment or flame. VAPORS MAY IGNITE AND EXPLODE. DO NOT SMOKE.** Ventilate area. Open doors and windows. Wear chemical resistant gloves/goggles/clothing. In absence of proper ventilation use properly fitted NIOSH respirator. Confine spill, collect using noncombustible absorbent material and place in properly sealed container. Dispose of excess product in accordance with applicable local, state and federal regulations.

## OTHER RESTRICTIONS

See Legal Disclaimer.

## LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at [usa.sika.com](http://usa.sika.com) or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.

### Sika Corporation

201 Polito Avenue  
Lyndhurst, NJ 07071  
Phone: +1-800-933-7452  
Fax: +1-201-933-6225  
[usa.sika.com](http://usa.sika.com)



### Product Data Sheet

Sikafloor® WP-8  
January 2023, Version 01.02  
020812040020000062

SikafloorWP-8-en-US-(01-2023)-1-2.pdf