



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2018

Reviewed on 08/03/2015

1 Identification

- **Product identifier**
- **Trade name:** Epalam 2026 Hardener
- **Article number:** RZ30074-1
- **Application of the substance / the mixture** Hardening agent/ Curing agent
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**
Company Name: Axson Technologies US, Inc.-SikaAxson

Headquarters:
31200 Stephenson Hwy
Madison Heights, MI 48071
USA

Manufacturing Site:
1611 Hults Drive
Eaton Rapids, MI 48827
USA
ehs-us@axson.com

- **Information department:** Product safety department
- **Emergency telephone number:**
During normal opening times: +1 (248) 588-2270
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS06 Skull and crossbones

Acute Tox. 3 H311 Toxic in contact with skin.

Acute Tox. 1 H330 Fatal if inhaled.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS09 Environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

(Contd. on page 2)

US

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: Epolam 2026 Hardener

(Contd. of page 1)

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS06 GHS09

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)

- **Hazard statements**

Harmful if swallowed.

Toxic in contact with skin.

Fatal if inhaled.

Causes severe skin burns and eye damage.

Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment is urgent (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 1

Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH 3 Health = 3

FIRE 1 Fire = 1

REACTIVITY 0 Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

US

(Contd. on page 3)

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: *Epalam 2026 Hardener*

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)
- **Identification number(s)**
- **EC number:** 229-962-1
- **Index number:** 612-110-00-1
- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 6864-37-5	2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	50-100%
EINECS: 229-962-1		

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Remove breathing apparatus only after contaminated clothing have been completely removed.
In case of irregular breathing or respiratory arrest provide artificial respiration.
- **After inhalation:**
Supply fresh air or oxygen; call for doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:**
Immediately call a doctor.
Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Mouth respiratory protective device.
Wear self-contained respiratory protective device.

(Contd. on page 4)

US

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: Epolam 2026 Hardener

(Contd. of page 3)

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures
· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals
· PAC-1:

6864-37-5	2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	0.28 mg/m ³
-----------	---	------------------------

· PAC-2:

6864-37-5	2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	3.1 mg/m ³
-----------	---	-----------------------

· PAC-3:

6864-37-5	2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)	19 mg/m ³
-----------	---	----------------------

7 Handling and storage
· Handling:
· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities
· Storage:
· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection
· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: Epolam 2026 Hardener

(Contd. of page 4)

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:

Liquid

Color:

Light amber

- **Odor:**

Like ammoniac

(Contd. on page 6)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: *Epalam 2026 Hardener*

(Contd. of page 5)

· Odor threshold:	<i>Not determined.</i>
· pH-value at 20 °C (68 °F):	<i>11</i>
· Change in condition	
Melting point/Melting range:	<i>-7 °C (19.4 °F)</i>
Boiling point/Boiling range:	<i>1,013 °C (1,855.4 °F)</i>
· Flash point:	<i>140 °C (284 °F)</i>
· Flammability (solid, gaseous):	<i>Not applicable.</i>
· Ignition temperature:	<i>275 °C (527 °F)</i>
· Decomposition temperature:	<i>Not determined.</i>
· Auto igniting:	<i>Product is not selfigniting.</i>
· Danger of explosion:	<i>Product does not present an explosion hazard.</i>
· Explosion limits:	
Lower:	<i>0.5 Vol %</i>
Upper:	<i>2.8 Vol %</i>
· Vapor pressure at 30 °C (86 °F):	<i>0 hPa (0 mm Hg)</i>
· Density at 20 °C (68 °F):	<i>0.94 g/cm³ (7.84 lbs/gal)</i>
· Relative density	<i>Not determined.</i>
· Vapor density	<i>Not determined.</i>
· Evaporation rate	<i>Not determined.</i>
· Solubility in / Miscibility with	
Water at 20 °C (68 °F):	<i>3.6 g/l</i>
· Partition coefficient (n-octanol/water):	<i>Not determined.</i>
· Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
· Solvent content:	
Water:	<i>1.0 %</i>
VOC content:	<i>0.00 %</i>
	<i>0.0 g/l / 0.00 lb/gl</i>
Solids content:	<i>0.0 %</i>
· Other information	<i>No further relevant information available.</i>

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*

(Contd. on page 7)

US



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: *Epalam 2026 Hardener*

(Contd. of page 6)

· **Hazardous decomposition products:**

?

Carbon monoxide and carbon dioxide

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)

Oral	LD50	320-460 mg/kg (rat)
Dermal	LD50	200-400 mg/kg (rabbit)
Inhalative	LC50/4 h	0.42 mg/l (rat) (Test Guideline 402)

· **Primary irritant effect:**

· **on the skin:** Strong caustic effect on skin and mucous membranes.

· **on the eye:**

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Toxic

Harmful

Corrosive

Irritant

Very toxic

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

6864-37-5 2,2'-dimethyl-4,4'methylenebis(cyclohexylamine)

48 hr EC50 15.2 mg/l (daphnia)

96 hr LC50 45 mg/l (Fish)

· **Persistence and degradability** No further relevant information available.

(Contd. on page 8)



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: Epolam 2026 Hardener

(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
*Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Must not reach bodies of water or drainage ditch undiluted or unneutralized.
 Danger to drinking water if even extremely small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms*
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, IMDG, IATA** UN2922
- **UN proper shipping name**
- **DOT** Corrosive liquids, toxic, n.o.s. (Cycloaliphatic Amine)
- **IMDG** CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amine),
MARINE POLLUTANT
- **IATA** CORROSIVE LIQUID, TOXIC, N.O.S. (Cycloaliphatic Amine)
- **Transport hazard class(es)**
- **DOT**
-
- **Class** 8 Corrosive substances

(Contd. on page 9)

US

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: *Epalam 2026 Hardener*

(Contd. of page 8)

 · **Label** 8, 6.1

 · **IMDG**

 · **Class** 8 Corrosive substances
 · **Label** 8/6.1

 · **IATA**

 · **Class** 8 Corrosive substances
 · **Label** 8 (6.1)

 · **Packing group**
 · **DOT, IMDG, IATA** II

 · **Environmental hazards:**
 · **Marine pollutant:** Yes
 Symbol (fish and tree)

 · **Special precautions for user** Warning: Corrosive substances
 · **Danger code (Kemler):** 886
 · **EMS Number:** F-A,S-B
 · **Stowage Category** B
 · **Stowage Code** SW2 Clear of living quarters.

 · **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

 · **Transport/Additional information:**

 · **DOT**
 · **Quantity limitations** On passenger aircraft/rail: 0.5 L
 On cargo aircraft only: 2.5 L
 · **Remarks:** Special marking with the symbol (fish and tree).

 · **IMDG**

 · **Limited quantities (LQ)** 0
 · **Excepted quantities (EQ)** Code: E0
 Not permitted as Excepted Quantity

 · **UN "Model Regulation":** UN 2922 CORROSIVE LIQUIDS, TOXIC, N.O.S. (CYCLOALIPHATIC AMINE), 8 (6.1), II, ENVIRONMENTALLY HAZARDOUS

US

(Contd. on page 10)

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: Epolam 2026 Hardener

(Contd. of page 9)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act) (Substances not listed):**

All ingredients are listed.

- **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

- **Chemical regulated by TSCA 5(a)(2) rule:**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **Listed in CWC Regulations**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05 GHS06 GHS09

- **Signal word** Danger

- **Hazard-determining components of labeling:**

2,2'-dimethyl-4,4'-methylenebis(cyclohexylamine)

(Contd. on page 11)

US



BUILDING TRUST



Safety Data Sheet

acc. to OSHA HCS

Printing date 05/07/2018

Reviewed on 08/03/2015

Trade name: Epolam 2026 Hardener

(Contd. of page 10)

· **Hazard statements**

*Harmful if swallowed.
Toxic in contact with skin.
Fatal if inhaled.
Causes severe skin burns and eye damage.
Toxic to aquatic life with long lasting effects.*

· **Precautionary statements**

*Do not breathe dusts or mists.
Wear protective gloves/protective clothing/eye protection/face protection.
[In case of inadequate ventilation] wear respiratory protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
Specific treatment is urgent (see on this label).
Take off immediately all contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** 05/07/2018 / 3

· **Abbreviations and acronyms:**

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
NIOSH: National Institute for Occupational Safety
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 1: Acute toxicity – Category 1
Skin Corr. 1A: Skin corrosion/irritation – Category 1A
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*