

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

### 1 Identification

- **Product identifier**
- **Trade name:** P14 Ultra White
- **Article number:** I011011-1
- **Application of the substance / the mixture** Polyester filler
- **Details of the supplier of the safety data sheet** SikaAxson US - EHS Department
- **Manufacturer/Supplier:**  
Supplier's Name: Sika Advanced Resins, US  
Headquarters:  
30800 Stephenson Hwy  
Madison Heights, MI 48071  
USA  
  
ehs-us@axson.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
During normal opening times: +1 (248) 588-2270  
CHEMTREC 24-hour Emergency: +1 (800) 424-9300

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: P14 Ultra White

(Contd. of page 1)

## · Hazard pictograms



GHS02 GHS07 GHS08

· Signal word *Danger*

## · Hazard-determining components of labeling:

Styrene

## · Hazard statements

*Flammable liquid and vapor.**Causes skin irritation.**Causes serious eye irritation.**Suspected of causing cancer.**Suspected of damaging fertility or the unborn child.**Causes damage to the hearing organs through prolonged or repeated exposure.*

## · Precautionary statements

*Avoid breathing dust/fume/gas/mist/vapors/spray**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*

## · Classification system:

## · NFPA ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

## · HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

## · Other hazards

## · Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: P14 Ultra White

· vPvB: Not applicable.

(Contd. of page 2)

### 3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 100-42-5	Styrene	10-20%
EINECS: 202-851-5		

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:**  
Mouth respiratory protective device.  
Wear self-contained respiratory protective device.
- **Additional information**  
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

(Contd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: P14 Ultra White

(Contd. of page 3)

### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

100-42-5	Styrene	20 ppm
7727-43-7	barium sulphate, natural	15 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	30 mg/m <sup>3</sup>
546-93-0	Magnesite	45 mg/m <sup>3</sup>
65997-17-3	Fibrous Glass	15 mg/m <sup>3</sup>
112945-52-5	Fumed silica - untreated	18 mg/m <sup>3</sup>
64-17-5	ethanol	1,800 ppm
21645-51-2	aluminium hydroxide	8.7 mg/m <sup>3</sup>
7759-02-6	strontium sulphate	30 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	18 mg/m <sup>3</sup>
112926-00-8	Precipitated silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
108-10-1	4-methylpentan-2-one	75 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	0.075 mg/m <sup>3</sup>
142-82-5	heptane	500 ppm
108-44-1	m-toluidine	6 ppm
100-41-4	ethylbenzene	33 ppm

· **PAC-2:**

100-42-5	Styrene	130 ppm
7727-43-7	barium sulphate, natural	170 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	330 mg/m <sup>3</sup>
546-93-0	Magnesite	260 mg/m <sup>3</sup>
65997-17-3	Fibrous Glass	170 mg/m <sup>3</sup>
112945-52-5	Fumed silica - untreated	100 mg/m <sup>3</sup>

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

**Trade name: P14 Ultra White**

(Contd. of page 4)

64-17-5	ethanol	3300* ppm
21645-51-2	aluminium hydroxide	73 mg/m <sup>3</sup>
7759-02-6	strontium sulphate	330 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	740 mg/m <sup>3</sup>
112926-00-8	Precipitated silica (Silica-Amorphous)	200 mg/m <sup>3</sup>
108-10-1	4-methylpentan-2-one	500 ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	33 mg/m <sup>3</sup>
142-82-5	heptane	830 ppm
108-44-1	m-toluidine	8.2 ppm
100-41-4	ethylbenzene	1100* ppm

**· PAC-3:**

100-42-5	Styrene	1100* ppm
7727-43-7	barium sulphate, natural	990 mg/m <sup>3</sup>
13463-67-7	titanium dioxide	2,000 mg/m <sup>3</sup>
546-93-0	Magnesite	1,600 mg/m <sup>3</sup>
65997-17-3	Fibrous Glass	990 mg/m <sup>3</sup>
112945-52-5	Fumed silica - untreated	630 mg/m <sup>3</sup>
64-17-5	ethanol	15000* ppm
21645-51-2	aluminium hydroxide	440 mg/m <sup>3</sup>
7759-02-6	strontium sulphate	2,000 mg/m <sup>3</sup>
7631-86-9	silicon dioxide, chemically prepared	4,500 mg/m <sup>3</sup>
112926-00-8	Precipitated silica (Silica-Amorphous)	1,200 mg/m <sup>3</sup>
108-10-1	4-methylpentan-2-one	3000* ppm
14808-60-7	Quartz (SiO <sub>2</sub> )	200 mg/m <sup>3</sup>
142-82-5	heptane	5000* ppm
108-44-1	m-toluidine	54 ppm
100-41-4	ethylbenzene	1800* ppm

### 7 Handling and storage

**· Handling:**
**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.

**· Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

(Contd. on page 6)

US



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

**Trade name: P14 Ultra White**

(Contd. of page 5)

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**100-42-5 Styrene**

ACGIH TLV	Short-term value: 170 at 40 ppm mg/m <sup>3</sup> Long-term value: 85 at 20 ppm mg/m <sup>3</sup>
OSHA PEL	Long-term value: 100 ppm mg/m <sup>3</sup> Ceiling limit value: 200 ppm mg/m <sup>3</sup>
PEL	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m <sup>3</sup> , 100 ppm Long-term value: 215 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: (170) mg/m <sup>3</sup> , (40) ppm Long-term value: (85) NIC-8.5 mg/m <sup>3</sup> , (20) NIC-2 ppm BEI, NIC-A3, NIC-OTO

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the eyes and skin.
- **Breathing equipment:**  
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 7)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

**Trade name: P14 Ultra White**

(Contd. of page 6)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

**9 Physical and chemical properties**

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	Pasty
· <b>Color:</b>	White
· <b>Odor:</b>	Pungent
· <b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· <b>Melting point/Melting range:</b>	Undetermined.
· <b>Boiling point/Boiling range:</b>	145 °C (293 °F)

· **Flash point:** 31 °C (87.8 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 490 °C (914 °F)

· **Decomposition temperature:** Not determined.

(Contd. on page 8)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: P14 Ultra White

(Contd. of page 7)

· <b>Auto igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
Lower:	0.9 Vol %
Upper:	6.8 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	6 hPa (4.5 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	2.16 g/cm <sup>3</sup> (18.03 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
Dynamic:	Not determined.
Kinematic:	Not determined.
· <b>Solvent content:</b>	
Organic solvents:	0.3 %
VOC content:	14.76 %
	319.5 g/l / 2.67 lb/gal
Solids content:	56.4 %
· <b>Other information</b>	No further relevant information available.

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

(Contd. on page 9)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: P14 Ultra White

(Contd. of page 8)

### 11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

- LD/LC50 values that are relevant for classification:

#### 100-42-5 Styrene

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4 h	11.8 mg/l (rat)

- Primary irritant effect:
  - on the skin: Irritant to skin and mucous membranes.
  - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:
 

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)

14807-96-6	Talc (Mg <sub>3</sub> H <sub>2</sub> (SiO <sub>3</sub> ) <sub>4</sub> )	3
100-42-5	Styrene	2B
13463-67-7	titanium dioxide	2B
64-17-5	ethanol	1
7631-86-9	silicon dioxide, chemically prepared	3
112926-00-8	Precipitated silica (Silica-Amorphous)	3
108-10-1	4-methylpentan-2-one	2B
14808-60-7	Quartz (SiO <sub>2</sub> )	1
100-41-4	ethylbenzene	2B

- NTP (National Toxicology Program)

14808-60-7	Quartz (SiO <sub>2</sub> )	K
------------	----------------------------	---

- OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential: No further relevant information available.

(Contd. on page 10)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

**Trade name: P14 Ultra White**



(Contd. of page 9)

- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**
- **DOT, IMDG, IATA** UN1866
- **UN proper shipping name**
- **DOT** Resin solution
- **IMDG, IATA** RESIN SOLUTION
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **IMDG, IATA**
- 
- **Class** 3 Flammable liquids

(Contd. on page 11)



**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

Trade name: P14 Ultra White

(Contd. of page 10)

· <b>Label</b>	3
· <b>Packing group</b> · <b>DOT, IMDG, IATA</b>	III
· <b>Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b> · <b>EMS Number:</b> · <b>Stowage Category</b>	Warning: Flammable liquids F-E, <u>S-E</u> A
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>UN "Model Regulation":</b>	UN 1866 RESIN SOLUTION, 3, III

**15 Regulatory information**

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

100-42-5 Styrene

· **TSCA (Toxic Substances Control Act): (Substances not listed)**

All ingredients are listed.

· **Chemicals regulated by TSCA Section 12(b)**

None of the ingredients is listed.

· **Chemical regulated by TSCA 5(a)(2)rule:**

None of the ingredients is listed.

· **Hazardous Air Pollutants**

100-42-5 Styrene

108-10-1 4-methylpentan-2-one

100-41-4 ethylbenzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-42-5 Styrene

13463-67-7 titanium dioxide

108-10-1 4-methylpentan-2-one

14808-60-7 Quartz (SiO<sub>2</sub>)

(Contd. on page 12)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

**Trade name: P14 Ultra White**

(Contd. of page 11)

100-41-4	ethylbenzene
----------	--------------

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

**· Chemicals known to cause developmental toxicity:**

64-17-5	ethanol
108-10-1	4-methylpentan-2-one

**· Carcinogenic categories**

**· EPA (Environmental Protection Agency)**

7727-43-7	barium sulphate, natural	D, CBD(inh), NL(oral)
108-10-1	4-methylpentan-2-one	I
142-82-5	heptane	D
100-41-4	ethylbenzene	D

**· TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc (Mg3H2(SiO3)4)	A4
13463-67-7	titanium dioxide	A4
64-17-5	ethanol	A3
14808-60-7	Quartz (SiO2)	A2
108-44-1	m-toluidine	A4
100-41-4	ethylbenzene	A3

**· NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
14808-60-7	Quartz (SiO2)

**· Listed in CWC Regulations**

None of the ingredients is listed.

**· GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms**



GHS02    GHS07    GHS08

**· Signal word** Danger

**· Hazard-determining components of labeling:**

Styrene

(Contd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 03/19/2019

Reviewed on 03/19/2019

**Trade name: P14 Ultra White**

(Contd. of page 12)

· **Hazard statements**

- Flammable liquid and vapor.
- Causes skin irritation.
- Causes serious eye irritation.
- Suspected of causing cancer.
- Suspected of damaging fertility or the unborn child.
- Causes damage to the hearing organs through prolonged or repeated exposure.

· **Precautionary statements**

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Do not breathe dust/fume/gas/mist/vapors/spray.
- Wear protective gloves/protective clothing/eye protection/face protection.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Store in a well-ventilated place. Keep cool.
- Store locked up.
- Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Date of preparation / last revision** 03/19/2019 / 11

· **Abbreviations and acronyms:**

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- NIOSH: National Institute for Occupational Safety
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- Flam. Liq. 3: Flammable liquids – Category 3
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- Carc. 2: Carcinogenicity – Category 2

(Contd. on page 14)



**Safety Data Sheet**  
*acc. to OSHA HCS*

Printing date 03/19/2019

Reviewed on 03/19/2019

**Trade name: P14 Ultra White**

(Contd. of page 13)

*Repr. 2: Reproductive toxicity – Category 2*  
*STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1*  
**· \* Data compared to the previous version altered.**

US