

Revision Date 07/25/2017

#### 1. Identification

Product name : Sikalastic®-395 Part B

Supplier : Sika Corporation

201 Polito Avenue Lyndhurst, NJ 07071

USA

www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300

INTERNATIONAL: 703-527-3887

Recommended use of the chemical and restrictions on

use

For further information, refer to product data sheet.

#### 2. Hazards identification

### **GHS Classification**

Acute toxicity, Category 4 (Oral) H302: Harmful if swallowed.

Skin corrosion, Category 1C H314: Causes severe skin burns and eye damage.

Serious eye damage, Category 1 H318: Causes serious eye damage.
Skin sensitization, Category 1 H317: May cause an allergic skin reaction.

Specific target organ systemic toxicity - H373: May cause damage to organs through repeated exposure, Category 2 (Oral) prolonged or repeated exposure if swallowed.

# **GHS** label elements

Hazard pictograms :







Signal Word : Danger

Hazard Statements : H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or

repeated exposure if swallowed.

Precautionary Statements : **Prevention:** 

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P270 Do not eat, drink or smoke when using this product.
P272 Contaminated work clothing must not be allowed out of



Revision Date 07/25/2017

Print Date 07/25/2017

the workplace.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

### Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

### Storage:

P405 Store locked up.

## Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.

There are no hazards not otherwise classified that have been identified during the classification process.

There are no ingredients with unknown acute toxicity used in a mixture at a concentration >= 1%.

#### 3. Composition/information on ingredients

## Hazardous ingredients

Chemical name	CAS-No.	Concentration (%)
diethylmethylbenzenediamine	68479-98-1	>= 25 - < 50 %
Isophorondiamine-Isobutyraldimine	54914-37-3	>= 25 - < 50 %
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	>= 2 - < 5 %
Hydroxyphenyl-benzotriazol derivates	104810-47-1	>= 2 - < 5 %
Poly(oxy-1,2-ethanediyl), .alpha[3-[3-(2H-	104810-48-2	>= 2 - < 5 %
benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-		
hydroxyphenyl]-1-oxopropyl]omegahydroxy-		
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	>= 1 - < 2 %

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4. First aid measures

If inhaled : Move to fresh air.



Revision Date 07/25/2017 Print Date 07/25/2017

Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.

Wash off with soap and plenty of water.

Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with

difficulty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If swallowed : Clean mouth with water and drink afterwards plenty of water.

Do not induce vomiting without medical advice.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed

: Health injuries may be delayed.

corrosive effects sensitizing effects

Gastrointestinal discomfort

Allergic reactions

Dermatitis

See Section 11 for more detailed information on health effects

and symptoms.

Harmful if swallowed.

May cause an allergic skin reaction.

Causes serious eye damage.

May cause damage to organs through prolonged or repeated

exposure if swallowed. Causes severe burns.

Protection of first-aiders : Move out of dangerous area.

Consult a physician.

Show this material safety data sheet to the doctor in

attendance.

Notes to physician : Treat symptomatically.

### 5. Fire-fighting measures

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Specific extinguishing

methods

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.



Revision Date 07/25/2017

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

for fire-fighters

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Environmental precautions : Use personal protective equipment. Deny access to unprotected persons.

: Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

## 7. Handling and storage

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see

section 8).

Do not get in eyes, on skin, or on clothing. For personal protection see section 8.

Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is

being used.

Smoking, eating and drinking should be prohibited in the

application area.

Follow standard hygiene measures when handling chemical

products.

Conditions for safe storage Store in original container.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Store in accordance with local regulations.

Materials to avoid : No data available

## 8. Exposure controls/personal protection

Contains no substances with occupational exposure limit values.

**Engineering measures** : Use of adequate ventilation should be sufficient to control

worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any



Revision Date 07/25/2017 Print Date 07/25/2017

recommended or statutory limits.

#### Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed

respirator complying with an approved standard if a risk

assessment indicates this is necessary.

The filter class for the respirator must be suitable for the

maximum expected contaminant concentration

(gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained

breathing apparatus must be used.

Hand protection

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Eye protection : Safety eyewear complying with an approved standard should

be used when a risk assessment indicates this is necessary.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hygiene measures : Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the

product.

Remove contaminated clothing and protective equipment

before entering eating areas. Wash thoroughly after handling.

## 9. Physical and chemical properties

Appearance : liquid
Color : clear

Odor : amine-like

Odor Threshold : No data available

Flash point :  $> 200 \, ^{\circ}\text{F} \, (> 93.33 \, ^{\circ}\text{C})$ 

Ignition temperature : No data available

Decomposition temperature : No data available

Lower explosion limit (Vol%) : No data available

Upper explosion limit (Vol%) : No data available

Flammability (solid, gas) : No data available



#### Revision Date 07/25/2017

Oxidizing properties : No data available

pH : Note: Not applicable

Melting point/range /

Freezing point

: No data available

Boiling point/boiling range : No data available

Vapor pressure : 0.4 mmHg (0.5 hpa)

: ca.0.93 g/cm3

at 73 °F (23 °C)

Water solubility : Note: insoluble

Partition coefficient: n-

octanol/water

Density

No data available

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm2/s

at 104 °F (40 °C)

Relative vapor density : No data available

Evaporation rate : No data available

Burning rate : No data available

Volatile organic compounds

(VOC) content

6.18 g/l

Sikalastic®-395 Part A + Part B Combined

: 4.24 g/l

Sikalastic®-395 Textured Part A + Part B + Sikalastic®-395

Textured Part C Combined

### 10. Stability and reactivity

Reactivity : No dangerous reaction known under conditions of normal use.

Chemical stability : The product is chemically stable.

Possibility of hazardous

reactions

: Stable under recommended storage conditions.

Conditions to avoid : No data available

Incompatible materials : No data available

### 11. Toxicological information

# **Acute toxicity**

Harmful if swallowed.

**Ingredients:** 



Revision Date 07/25/2017 Print Date 07/25/2017

diethylmethylbenzenediamine:

Acute oral toxicity : LD50 Oral (Rat): 738 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 2,500 mg/kg

Isophorondiamine-Isobutyraldimine:

Acute oral toxicity : LD50 Oral (Rat): 4,150 mg/kg

Skin corrosion/irritation

Causes severe burns.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure if swallowed.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity** 

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Not applicable

NTP Not applicable

# 12. Ecological information

Other information Do not empty into drains; dispose of this material and its

container in a safe way.

Avoid dispersal of spilled material and runoff and contact

with soil, waterways, drains and sewers.

Toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

May be harmful to the environment if released in large

quantities.

Water polluting material.



Revision Date 07/25/2017

### 13. Disposal considerations

**Disposal methods** 

Waste from residues : Disposal of this product, solutions and any by-products should

at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

### 14. Transport information

DOT

UN number 1760

Description of the goods Corrosive liquids, n.o.s.

(Isophorondiamine-Isobutyraldimine)

Class 8
Packing group III
Labels 8
Emergency Response 154

Guidebook Number

IATA

UN number 1760

Description of the goods Corrosive liquid, n.o.s.

(Isophorondiamine-Isobutyraldimine,

diethylmethylbenzenediamine)

Class 8
Packing group III
Labels 8
Packing instruction (cargo 856

aircraft)

Packing instruction 852

(passenger aircraft)

Packing instruction Y841

(passenger aircraft)

**IMDG** 

UN number 1760

Description of the goods CORROSIVE LIQUID, N.O.S.

(Isophorondiamine-Isobutyraldimine,

diethylmethylbenzenediamine)

Class 8
Packing group III
Labels 8
EmS Number 1 F-A
EmS Number 2 S-B

Marine pollutant yes



Revision Date 07/25/2017

DOT: For Limited Quantity exceptions reference 49 CFR 173.154 (b)

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

#### Special precautions for user

No data available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

### 15. Regulatory information

**TSCA list** : All chemical substances in this product are either listed on the

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

## **EPCRA - Emergency Planning and Community Right-to-Know**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

## **SARA304** Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Chronic Health Hazard

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

**SARA 302** : This material does not contain any components with a section

302 EHS TPQ.

**SARA 313** : This material does not contain any chemical components with

> known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

**Ozone-Depletion** 

This product neither contains, nor was manufactured with a **Potential** 

Class I or Class II ODS as defined by the U.S. Clean Air Act

Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

California Prop 65 This product does not contain any chemicals known to the State



Revision Date 07/25/2017

Print Date 07/25/2017

of California to cause cancer, birth, or any other reproductive defects.

#### 16. Other information

#### **HMIS Classification**



**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

#### **Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 07/25/2017

Material number: 495527