

SikaTile®-885 Secure Silicone Caulk

HIGH PERFORMANCE, HYBRID SILICONE ADHESIVE AND SEALANT

- For filling joints where tile abuts different surfaces or planes
- Flexible filler between horizontal and vertical surfaces to prevent cracked tile due to expansion
- Formulated to match all SikaTile® grout colors
- Mold and mildew resistant
- Easy to tool and paintable
- Colors: 32 colors
- Packaging: 10.3 US fl. oz. (305 ml) cartridges (10 per carton)

Attributes Include:



BUILDING TRUST



SikaTile®-885 Secure Silicone Caulk

HIGH PERFORMANCE, HYBRID SILICONE ADHESIVE AND SEALANT

WHERE TO USE

- SikaTile®-885 Secure Silicone Caulk is used to fill joints up to 1/2" (12 mm) in width between panels, cracks, walls, around tubs, showers, sinks, counter tops, etc.
- For filling joints where tile abuts different surfaces or planes
- For expansion joints including traffic areas
- For interior and exterior, dry and wet applications in both residential and commercial applications

HOW TO USE

Use painter's tape or shield these areas for protection. Test in an inconspicuous area to determine if staining will occur. Caulking may be done either before or after grouting. Insert the tube into a standard caulking gun and cut off the tip of the tube at a slant to the desired size. Apply caulk into the opening using a continuous bead at a 45-degree angle.

COLORS AVAILABLE

00525 Black Sapphire



00162 True Taupe



00038 Gray



00340 Shark Fin



00034 River Rock



00035 Natural Gray



00330 Dolphin



00325 Vintage Pewter



00320 Dove Gray



00032 Light Taupe



00030 Silver




00312 Classic Silver



00310 Cloudy Gray




00125 Glacier




00010 Bright White




00120 Pearl




00111 Polar White




00121 Vanilla



00011 Snow White



00112 Pure White



00012 Navajo White



Smooth with a denatured alcohol or mineral spirits, wet putty knife, caulking tool, or gloved finger. Excess caulk should be removed with a damp cloth before the caulk skins over. When applied in areas exposed to moisture allow the caulking to cure a minimum of 72 hours at 70° F (21° C) prior to putting the area into use. Complete cure is achieved in 14 to 28 days depending on ambient temperature and humidity.


COVERAGE	
Joint Size	Approximate Coverage*
1/4" (6 mm) x 1/4" (6 mm)	24 lin. ft. (7.5 m)
1/4" (6 mm) x 1/2" (12 mm)	12 lin. ft. (3.8 m)

*Coverage shown is for estimating purposes only. Actual coverage may vary due to installation techniques, actual tile types, sizes, and waste used on the job.

00210 Blanched Almond



00017 Bone



00220 Sand Drift



00018 Cream



00021 Canvas



00230 Baja



00025 Tumbleweed




00153 Buckskin




00150 Santa Fe



00191 Terracotta



00175 Dark Chocolate



FOR MORE INFORMATION:

Contact Sika:

Phone 800.933.SIKA(7452)

Website: www.SikaTile.com

Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
Phone: 201-933-8800
Fax: 201-933-6225

BUILDING TRUST

