Product Information



Sikagard® 740 W

Silane based reactive water repellent penetrating sealer







Product Information

APPLICATIONS

- Walkways and ramps
- ▲ Industrial floors
- Exposed aggregate
- ▲ Precast or pre-placed concrete
- Masonry
- ▲ Parking decks
- ▲ Stadiums

ADVANTAGES

- ▲ Good penetration
- ▲ Economic and easy to use
- ▲ Independent test data available
- Reduces capillary water absorption, protection against driving rain and splashing on vertical areas.
- Reduction of absorption of aggressive or deleterious agents dissolved in water (i.e. chlorides)
- Increases the resistance of concrete to freeze and thaw cycles and de-icing salts
- ▲ Water based emulsion, Low VOC
- Resistant to sea water
- A Ready and easy to use

TYPICAL DATA

- ▲ Shelf Life: 9 months from date of production
- ▲ Storage Conditions: Store in unopened, undamaged and original sealed packaging in dry and cool conditions. Protect from moisture
- ▲ Product Conditioning: Condition material between 40°F and
- ▲ Sealer Type: Silane
- ▲ Active Ingredient Content: 40%
- ▲ Base: Water emulsion
- ▲ VOC: <350 g/l
- ▲ Depth of Penetration OHD L-34: <10 mm
- * For up to date and accurate information please consult the current Technical Data Sheet at www.sikausa.com

Sikagard® 740 W

Silane based reactive water repellent penetrating sealer



Estimation of material consumption for different test areas



Selection of the best application tools



Extracting core



Confirming penetration depth

Contact Sika at:

Phone: 1-800-933-SIKA (Nationwide)

Website: www.sikausa.com

Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071 Phone: 201-933-8800 Fax: 201-933-6225 Sika Canada Inc. 601 Delmar Avenue Pointe Claire Quebec H9R 4A9 Phone: 514-697-2610

Fax: 514-694-2792







Sika Mexicana S.A. de C.V. Carretera Libre Celaya Km. 8.5 Fracc. Industrial Balvanera Corregidora, Queretaro C.P. 76920

Phone: 52 442 2385800 Fax: 52 442 2250537