

PRODUCT DATA SHEET

Sikalastic® P 255

(formerly MasterSeal® P 255)

POLYURETHANE-BASED PRIMER FOR SIKALASTIC DECK COATING

PRODUCT DESCRIPTION

Sikalastic® P 255 is a two-component polyurethane-based adhesive primer for use in deck coating systems.

USES

- Stadiums
- Balconies
- Parking Garages
- Commercial Construction
- Building and Restoration
- Plywood Decks/Balconies
- Plaza Decks

CHARACTERISTICS / ADVANTAGES

- Sikalastic® P 255 is a primer for use with a two-component base coat
- Extremely fast cure time allowing for minimal downtime
- Strong adhesion when applied with Sikalastic M 265/ M 270 NP base coat

PRODUCT INFORMATION

Chemical Base	Sikalastic® P 255 is a fast-curing polyurethane-based adhesive primer.
Packaging	Sikalastic® P 255 <ul style="list-style-type: none"> ▪ 3.4 gallon (12.87 L) pails
Shelf Life	When properly stored, Sikalastic® P 255 products have the following shelf life: <ul style="list-style-type: none"> ▪ 3.4-Gallon Pail: 1.25 Years
Storage Conditions	Store in unopened containers in a cool, clean, dry area
Color	Clear/Amber
Solid content by volume	99%
Viscosity	630 cps* * Cold temperatures will increase viscosity.

TECHNICAL INFORMATION

SYSTEM INFORMATION

Systems

- Sikalastic® 1500 Pedestrian / Vehicular
- Sikalastic® 2500 Pedestrian / Vehicular
- Sikalastic® 2530 Vehicular
- Sikalastic® 2575 Vehicular
- Sikalastic® 2850 Vehicular

APPLICATION INFORMATION

Coverage

See preferred Sika Deck Coating Solution for total system yield

Cure Time

Sikalastic® P 255 cures in 2–3 hours when tested at 73 °F (23 °C) and 50% relative humidity

BASIS OF PRODUCT DATA

Results may differ based upon statistical variations depending upon mixing methods and equipment, temperature, application methods, test methods, actual site conditions and curing conditions.

ENVIRONMENTAL, HEALTH AND SAFETY

For further information and advice regarding transportation, handling, storage and disposal of chemical products, user should refer to the actual Safety Data Sheets containing physical, environmental, toxicological and other safety related data. User must read the current actual Safety Data Sheets before using any products. In case of an emergency, call CHEMTREC at 1-800-424-9300, International 703-527-3887.

APPLICATION INSTRUCTIONS

APPLICATION

Please see the preferred Sika Deck Coating Solution for total system and aggregate surface preparation and application. Sikalastic® P 255 is applied in conjunction with Sikalastic® M 265/ M 270 N base coat.

LEGAL DISCLAIMER

- KEEP CONTAINER TIGHTLY CLOSED
- KEEP OUT OF REACH OF CHILDREN
- NOT FOR INTERNAL CONSUMPTION
- FOR INDUSTRIAL USE ONLY
- FOR PROFESSIONAL USE ONLY

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates (“SIKA”), the user must always read and follow the warnings and instructions on the product’s most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA’s Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product’s shelf life. User determines suitability of product for intended use and assumes all risks. User’s and/or buyer’s sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and

Conditions of Sale which are available at
<https://usa.sika.com/en/group/SikaCorp/termsandconditions.html>
or by calling 1-800-933-7452.

Sika Corporation

201 Polito Avenue
Lyndhurst, NJ 07071
Phone: +1-800-933-7452
Fax: +1-201-933-6225
usa.sika.com



Product Data Sheet

Sikalastic® P 255
June 2024, Version 01.01
02081200000002057

SikalasticP255-en-US-(06-2024)-1-1.pdf

