

SIKA CORPORATION - ROOFING

WARRANTY SELECTION GUIDE

Warranty Duration ¹				
Membrane - Thickness	5 - 15 Years	20 Years	25 Years	30 Years
Sarnafil, G410 & S327 - 60 mil ^{2,3}	●	●	-	-
Sarnafil, G410 & S327 - 72 mil ^{2,3}	●	●	●	-
Sarnafil, G410 & S327 - 80 mil ^{2,3}	●	●	●	●
Sarnafil G410 SA - 60 mil	●	●	-	-
Sikaplan, Fastened & Adhered - 60 mil ²	●	●	-	-

Special Systems ¹¹				
5 - 15 Years	20 Years	25 Years	30 Years	
Décor (white, reflective gray, tan colors)	●	●	●	●
Décor (other colors)	●	●	-	-
RhinoBond	●	●	●	● ⁴
Hybrid	●	●	●	● ⁴
Recover	●	●	● ⁴	● ⁴

Accessories				
5 - 15 Years	20 Years	25 Years	30 Years	
Skylight ⁸ (watertightness)	●	●	-	-
Liquid Flashing (PMMA)	●	●	-	-
Liquid Flashing (RoofPro)	●	●	● ⁴	-
SarnaRoof ES-1 Edge Cleat	●	●	-	-

Wind Speed (up to) ¹							
System	Sheet Width	46 mph	60 mph	74 mph	99 mph	120 mph	Over 120 mph
Sarnafil Adhered ^{2,3}	all	-	●	●	●	●	-
Sarnafil G410 SA	6.5'	-	●	●	●	-	-
Sarnafil RhinoBond ³	all	-	●	●	●	● ⁴	-
Sarnafil S327 Sarnafast ^{2,3} In-Seam, Single Weld	5'	-	●	●	●	●	-
	6.5'	-	●	●	●	-	-
	10'	-	●	●	-	-	-
Sarnafil S327 Express ^{2,3} In-Seam, Double Weld	5' / 6.5'	-	●	●	●	●	-
	10'	-	●	●	●	-	-
Hybrid	all	-	●	●	●	-	-
Sarnafil S327 Engineered ^{2,3} Bar & Coverstrip	all	-	●	●	●	●	● ⁴

Sikaplan Adhered & Fastened ²	all	●	●	●	●	●	-
Sikaplan RhinoBond	all	●	●	●	●	●	-

Accessories	46 mph	60 mph	74 mph	99 mph	100-110 mph	111-120 mph	120> mph
ES-1 Tested or Sarnaclad 1-1	● ¹³	●	●	● ¹²	-	-	-
Sarnaclad High Wind 1-1A	● ¹³	●	●	●	● ¹²	● ¹²	-
SarnaRoof ES-1 Edge Cleat	●	●	●	-	-	-	-
Engineered Metal	● ¹³	●	●	●	●	● ¹²	● ⁴

Hail ¹			
Warranty Duration	Sarnafil Membrane / Sikaplan ¹⁴		
Years	1.5" System ⁵	2.0" Limited System ⁶	2.0" System ⁷
5	60 mil	N/A	60 mil
10	60 mil	N/A	60 mil
15	60 mil	60 mil	72 mil
20	60 -72mil (S327 only)	72 mil	80 mil

Warranty Duration	Skylight ^{8,9}	PMR Insulation Panel ^{8,10}	
Years	2.0"	2.0" (LightGuard®)	3.5" (HeavyGuard®)
5	●	●	●
10	●	●	●
15	●	●	●
20	-	●	●
25	-	● ⁴	● ⁴
30	-	● ⁴	● ⁴

¹ Requirements for deck and component securement must be met, additional enhancements may be required.

² Includes feltbacked membranes.

³ Includes textured membranes.

⁴ Special Warranty Request (SWR) required, written approval necessary by approved personnel within Corporate Technical.

⁵ Available for adhered systems & mech fastened systems; Gypsum cover board required below membrane.

⁶ Available for adhered systems & mech fastened systems; Gypsum cover board required below membrane; Replacement membrane only (no labor, no accessories).

⁷ Available for adhered systems & RhinoBond systems; Gypsum cover board required below membrane; Gypsum cover board must be adhered to underlying insulation in adhered systems.

⁸ Products must be purchased through Sika Corporation to be eligible for Sika warranty coverage.

⁹ Skylight hail coverage only, when used on Sikaplan membrane systems.

¹⁰ Sarnafil membrane only.

¹¹ Membrane and Thickness requirements must be met.

¹² Requires 3 ft Perimeter bar.

¹³ Sikaplan membrane Only

¹⁴ Sikaplan membrane maximum Hail offering 3/4" with a maximum warranty duration of 20 Years