



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

SECTION 1. IDENTIFICATION

Product name : Sikafloor®-265 Part A

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H361 Suspected of damaging fertility or the unborn child.



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

Precautionary Statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P261 Avoid breathing mist or vapors.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:
 P405 Store locked up.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	$\geq 50 - < 70$
bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319	$\geq 10 - < 20$



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

weight 700-1100)		Skin Sens. 1; H317	
2,2-bis(acryloyloxymethyl)butyl acrylate	15625-89-5	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 5 - < 10
oxirane, mono[(C12-14-alkyloxy)methyl]derivatives	68609-97-2	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 5 - < 10
Phenol, 4-nonyl, branched	84852-15-3	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Repr. 2; H361	>= 1 - < 5
bisphenol-F-(epichlorhydrin) epoxy resin	9003-36-5	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 1 - < 5
Benzyl alcohol	100-51-6	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2A; H319	>= 1 - < 5
P-tert-butylphenyl-1-(2,3-epoxy)propyl ether	3101-60-8	Skin Sens. 1; H317	>= 1 - < 5
Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	64742-47-8	Asp. Tox. 1; H304	>= 1 - < 5

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and : irritant effects
sensitizing effects



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

- Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

- Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

- Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : opaque

Odor : characteristic

Odor Threshold : No data available

pH : Not applicable

Melting point/range / Freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 201 °F / 94 °C
(Method: closed cup)

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : 0.01 hpa

Relative vapor density : No data available

Density : ca. 1.1 g/cm³ (73 °F / 23 °C)

Solubility(ies)

 Water solubility : insoluble

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. > 20.5 mm ² /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	2 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700):

Acute oral toxicity	:	LD50 Oral (Rat): > 5,000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 20,000 mg/kg

2,2-bis(acryloyloxymethyl)butyl acrylate:

Acute oral toxicity	:	LD50 Oral (Rat): 3,680 - 5,000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5,000 mg/kg



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

Phenol, 4-nonyl, branched:

- Acute oral toxicity : LD50 Oral (Rat): 1,412 mg/kg
Acute dermal toxicity : LD50 Dermal (Rabbit): 3,160 mg/kg

Benzyl alcohol:

- Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

P-tert-butylphenyl-1-(2,3-epoxy)propyl ether:

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): 3,466 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 Dermal (Rabbit): 6,000 mg/kg

Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

- Method : In Vitro Membrane Barrier Test Method for Skin Corrosion -
CORROSITEX
Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

Not classified due to lack of data.

IARC	Group 2B: Possibly carcinogenic to humans	
	2-ethyl-2-[[[(1-oxoallyl)oxy]methyl]-1,3-propanediyl diacrylate	15625-89-5
	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide (> 10 µm)	13463-67-7

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

Not classified due to lack of data.

STOT-repeated exposure

Not classified due to lack of data.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Remarks : Titanium dioxide (13463-67-7)
In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
aquatic invertebrates Exposure time: 48 h

2,2-bis(acryloyloxymethyl)butyl acrylate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0.87 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Phenol, 4-nonyl, branched:

Benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l
aquatic invertebrates Exposure time: 48 h

Hydrocarbons, C13-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l
Exposure time: 96 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): >
plants 1,000 mg/l

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor- : Do not empty into drains; dispose of this material and its con-
mation tainer in a safe way.
Avoid dispersal of spilled material and runoff and contact with



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

soil, waterways, drains and sewers.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
May be harmful to the environment if released in large quantities.
Water polluting material.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

- UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(4-nonylphenol, branched, epoxy resin)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG-Code

- UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(4-nonylphenol, branched, epoxy resin)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Domestic regulation

49 CFR

Not regulated as a dangerous good



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

DOT: As per 49 CFR 171.4, Non-bulk materials (<119 Gal) are exempt from being classified as a Marine Pollutant.

IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet.

Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

The following substance(s) is/are subject to a Significant New Use Rule:

naphtha (petroleum), heavy alkylate	64741-65-7	See 40 CFR 721.11782; Proposed Rule
Phenol, 4-nonyl, branched	84852-15-3	See 40 CFR § 721.10765; Proposed Rule

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

Phenol, 4-nonyl, branched	84852-15-3
---------------------------	------------

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization
Reproductive toxicity
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Phenol, 4-nonyl, branched	84852-15-3	>= 1 - < 5 %
---------------------------	------------	--------------

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including 2,2-bis(acryloyloxymethyl)butyl acry-



Sikafloor®-265 Part A

Revision Date 04/04/2024

Print Date 04/04/2024

late, which is known to the State of California to cause cancer, and 4,4'-isopropylidenediphenol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 04/04/2024

000000604211
US / Z8